


## GERMANIUM DIODE

Germanium diode in all glass construction for use in a.m. detector circuits.  
Type 2-OA79 consists of 2 diodes OA79 selected for operation in a ratio detector circuit.

### MECHANICAL DATA

Dimensions in mm

The white band indicates the cathode side



### RATINGS (Limiting values) <sup>1)</sup>

|   |           |      |            |    |
|---|-----------|------|------------|----|
| Continuous reverse voltage                          | $V_R$     | max. | 30         | V  |
| Repetitive peak reverse voltage                     | $V_{RRM}$ | max. | 45         | V  |
| Forward current (d.c.)                              | $I_F$     | max. | 35         | mA |
| Repetitive peak forward current                     | $I_{FRM}$ | max. | 100        | mA |
| Non repetitive peak forward current ( $t \leq 1$ s) | $I_{FSM}$ | max. | 200        | mA |
| Operating ambient temperature                       | $T_{amb}$ |      | -50 to +60 | °C |

### CHARACTERISTICS

#### Forward voltage

$I_F = 0.1$  mA

|       | $T_{amb} = 25^\circ\text{C}$ | $T_{amb} = 60^\circ\text{C}$ |
|-------|------------------------------|------------------------------|
| $V_F$ | typ. 0.23<br>0.15 to 0.30    | typ. 0.16<br>0.1 to 0.25     |

$I_F = 10$  mA

|       |                        |                        |
|-------|------------------------|------------------------|
| $V_F$ | typ. 1.5<br>0.8 to 2.2 | typ. 1.4<br>0.7 to 2.1 |
|-------|------------------------|------------------------|

$I_F = 30$  mA

|       |                        |                        |
|-------|------------------------|------------------------|
| $V_F$ | typ. 2.8<br>1.4 to 4.0 | typ. 2.6<br>1.2 to 3.8 |
|-------|------------------------|------------------------|

#### Reverse current

$V_R = 0.1$  V

|       |                    |                  |
|-------|--------------------|------------------|
| $I_R$ | typ. 0.35<br>< 1.0 | typ. 4.5<br>< 12 |
|-------|--------------------|------------------|

$V_R = 1.5$  V

|       |                        |                     |
|-------|------------------------|---------------------|
| $I_R$ | typ. 0.8<br>0.1 to 2.8 | typ. 6<br>0.8 to 25 |
|-------|------------------------|---------------------|

$V_R = 10$  V

|       |                       |                      |
|-------|-----------------------|----------------------|
| $I_R$ | typ. 4.5<br>0.4 to 18 | typ. 16<br>2.5 to 60 |
|-------|-----------------------|----------------------|

$V_R = 30$  V

|       |                       |                      |
|-------|-----------------------|----------------------|
| $I_R$ | typ. 35<br>1.5 to 150 | typ. 60<br>60 to 300 |
|-------|-----------------------|----------------------|

$V_R = 45$  V

|       |                     |                       |
|-------|---------------------|-----------------------|
| $I_R$ | typ. 90<br>4 to 350 | typ. 170<br>15 to 500 |
|-------|---------------------|-----------------------|


<sup>1)</sup> Limiting values according to the Absolute Maximum System as defined in IEC publication 134.

7Z3 1247

# OA79 2-OA79

## APPLICATION INFORMATION

Measuring circuit at  $T_{amb} = 25^{\circ}C$



$$V_{I(RMS)} = 3 \text{ V}$$


$$f = 10.7 \text{ MHz}$$

$$\eta \text{ typ. } 85 \%$$

$$R_d \text{ typ. } 15 \text{ k}\Omega$$

$$R_d \text{ } 13.5 \text{ to } 19 \text{ k}\Omega$$

Diode in an a.m. detector circuit at  $T_{amb} = 25^{\circ}C$



$$V_{I(RMS)} = 0.1 \text{ V}$$


$$f = 0.5 \text{ MHz}$$

$$V_O \text{ typ. } 55 \text{ mV}$$

$$V_{O(rms)} \text{ typ. } 4.5 \text{ mV}^{1)}$$

$$R \text{ typ. } 40 \text{ k}\Omega^{2)}$$

Matched pair in a ratio detector circuit



$$L_p = 7.4 \text{ } \mu\text{H}$$

$$Q_0 = 80 \text{ unloaded}$$

$$R = 40 \text{ k}\Omega \text{ unloaded}$$

$$\text{Tap} = 0.5$$

$$L_s = 4.4 \text{ } \mu\text{H}$$

$$Q_0 = 150 \text{ unloaded}$$

$$R = 45 \text{ k}\Omega \text{ unloaded}$$

$$kQ = 0.8^{3)}$$

$$f_0 = 10.7 \text{ MHz}$$

$$\Delta f = 15 \text{ kHz}$$

$$m = 0.3$$

a.m. suppression factor at  $V_C = 2 \text{ to } 20 \text{ V}$

$$f = f_0$$

$$\alpha \geq 30$$

$$f = f_0 \pm 25 \text{ kHz}$$

$$\alpha \geq 15$$

For optimum a.m. suppression  $D_1$  must be that diode of the matched pair which has the better dynamic forward characteristic.

**For new design the successor types AA119; 2-AA119 are recommended**

1) Modulation factor  $m = 0.3$

2) Modulation factor  $m = 0$

3) Measured in the circuit with  $V_p = 350 \text{ mV}$

723 1909