TOSHIBA

TOSHIBA HIGH EFFICIENCY RECTIFIER SILICON EPITAXIAL TYPE

5 J L Z 4 7 A

SWITCHING TYPE POWER SUPPLY APPLICATION **CONVERTER & CHOPPER APPLICATION**

Repetitive Peak Reverse Voltage $: V_{RRM} = 600V$

 $: V_{\text{FM}} \!=\! 4.0 V$ Peak Forward Voltage

Ultra Fast Reverse-Recovery Time: trr=35ns

MAXIMUM RATINGS

CHARACTERISTIC	SYMBOL	RATING	UNIT
Repetitive Peak Reverse Voltage	v_{RRM}	600	V
Average Output Rectified Current	IO	5	A
Peak One Cycle Surge Forward Current (Non-Repetitive)	I_{FSM}	40	A
Junction Temperature	T_{j}	-40~150	°C
Storage Temperature Range	$T_{ m stg}$	-40~150	°C

Unit in mm 43.2 ± 0.2 0.75 ± 0.15 2.54 ± 0.25 2.54 ± 0.25 1. CATHODE 2. ANODE **JEDEC EIAJ** TOSHIBA 12-10C2

Weight: 2.0g

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Peak Forward Voltage	$ m V_{FM}$	$I_{\text{FM}} = 5A$	_	_	4.0	V
Repetitive Peak Reverse Current	I_{RRM}	$V_{RRM} = 600V$	_	_	50	μ A
Reverse Recovery Time	t_{rr}	$I_F=2A$, di/dt= $-20A/\mu s$	_		35	ns
Thermal Resistance	R _{th (j-c)}	DC	_	_	4.5	°C/W


The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.

The information contained herein is subject to change without notice.

TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.

The information contained herein is presented only as a guide for the applications of our products. No responsibility.

MARKING



※ Number	SYMBOL		MARK			
%1	Toshiba Product Mark		5			
%2	TYPE	5JLZ47A	5JLZ47			
*3		5JLZ47A	A			
※4	Polarity Mark		- ₩-			
	Lot Number					
※ 5	Month (Starting from Alphabet A)					
	Year (Last Number of the Christian Era)					

