



# TO-92 Plastic-Encapsulate Transistors

## A42 TRANSISTOR ( NPN )

### FEATURES

Power dissipation

$$P_{CM} : 0.625 \text{ W ( } T_{amb}=25 \text{ )}$$

Collector current


$$I_{CM} : 0.5 \text{ A}$$

Collector-base voltage

$$V_{(BR)CBO} : 300 \text{ V}$$

Operating and storage junction temperature range

$$T_J , T_{stg} : -55 \text{ to } +150$$






### ELECTRICAL CHARACTERISTICS ( $T_{amb}=25$ unless otherwise specified )

| Parameter                            | Symbol        | Test conditions  | MIN | TYP | MAX  | UNIT    |
|--------------------------------------|---------------|--|-----|-----|------|---------|
| Collector-base breakdown voltage     | $V_{(BR)CBO}$ | $I_C=100 \mu A, I_E=0$                                     | 300 |     |      | V       |
| Collector-emitter breakdown voltage  | $V_{(BR)CEO}$ | $I_C=1 \text{ mA}, I_B=0$                                  | 300 |     |      | V       |
| Emitter-base breakdown voltage       | $V_{(BR)EBO}$ | $I_E=100 \mu A, I_C=0$                                     | 5   |     |      | V       |
| Collector cut-off current            | $I_{CBO}$     | $V_{CB}=200 \text{ V}, I_E=0$                              |     |     | 0.25 | $\mu A$ |
| Emitter cut-off current              | $I_{EBO}$     | $V_{EB}=5 \text{ V}, I_C=0$                                |     |     | 0.1  | $\mu A$ |
| DC current gain                      | $h_{FE(1)}$   | $V_{CE}=10 \text{ V}, I_C=1 \text{ mA}$                    | 60  |     |      |         |
|                                      | $h_{FE(2)}$   | $V_{CE}=10 \text{ V}, I_C=10 \text{ mA}$                   | 80  |     | 250  |         |
|                                      | $H_{FE(3)}$   | $V_{CE}=10 \text{ V}, I_C=30 \text{ mA}$                   | 75  |     |      |         |
| Collector-emitter saturation voltage | $V_{CE(sat)}$ | $I_C=20 \text{ mA}, I_B=2 \text{ mA}$                      |     |     | 0.2  | V       |
| Base-emitter saturation voltage      | $V_{BE(sat)}$ | $I_C=20 \text{ mA}, I_B=2 \text{ mA}$                      |     |     | 0.9  | V       |
| Transition frequency                 | $f_T$         | $V_{CE}=20 \text{ V}, I_C=10 \text{ mA}, f=30 \text{ MHz}$ | 50  |     |      | MHz     |

### CLASSIFICATION OF $h_{FE(2)}$

| Rank  | A      | B <sub>1</sub> | B <sub>2</sub> | C       |
|-------|--------|----------------|----------------|---------|
| Range | 80-100 | 100-150        | 150-200        | 200-250 |

# Typical Characteristics



## TO-92 PACKAGE OUTLINE DIMENSIONS



| Symbol | Dimensions In Millimeters |        | Dimensions In Inches |       |
|--------|---------------------------|--------|----------------------|-------|
|        | Min                       | Max    | Min                  | Max   |
| A      | 3.300                     | 3.700  | 0.130                | 0.146 |
| A1     | 1.100                     | 1.400  | 0.043                | 0.055 |
| b      | 0.380                     | 0.550  | 0.015                | 0.022 |
| c      | 0.360                     | 0.510  | 0.014                | 0.020 |
| D      | 4.400                     | 4.700  | 0.173                | 0.185 |
| D1     | 3.430                     |        | 0.135                |       |
| E      | 4.300                     | 4.700  | 0.169                | 0.185 |
| e      | 1.270TYP                  |        | 0.050TYP             |       |
| e1     | 2.440                     | 2.640  | 0.096                | 0.104 |
| L      | 14.100                    | 14.500 | 0.555                | 0.571 |
| Ö      |                           | 1.600  |                      | 0.063 |
| ↓      | 0.000                     | 0.380  | 0.000                | 0.015 |