

AB-X29NXXX Series PECL/LVPECL UHF XO


Description

The **AB-X29NXXX Series** of crystal oscillators (XO) provides ultra high frequency with PECL/LVPECL complementary outputs. The outputs can be disabled for test automation or combining multiple clocks. The device is based on low noise analog harmonic frequency multiplication, providing exceptionally low Phase Noise and Jitter. It's packaged in a miniature, FR-4 based 9x14 mm SMD package

Applications and Features

- Fiber Channel; 10 GbE; Infiniband; Network Processors; SONET/SDH
- High Reliability – NEL HALT/HASS qualified for crystal oscillator start-up conditions
- Extremely Low Phase Noise and Jitter
- Frequency Range to 1,000 MHz
- RoHS compliant, Lead Free Construction
- SONET ± 20 ppm overall stability available
- High Shock Resistance, to 1.000 G

Creating a Part Number




**FREQUENCY
CONTROLS, INC.**

357 Beloit Street, P.O. Box 457, Burlington, WI 53105-0457 U.S.A. Phone 262/763-3591 FAX 262/763-2881

Email: nelsales@nelfc.com www.nelfc.com

AB-X29NXXX Series


Drawing Specification



Environmental and Mechanical Characteristics

Operating temp. range	see part # table
Mechanical Shock	Per MIL-STD-202, Method 213, Cond. A
Thermal Shock	Per MIL-STD-883, Method 1011, Cond. A
Vibration	Per MIL-STD-883, Method 2007, Cond. A
Hermetic Seal	Leak rate less than 1×10^{-8} atm.cc/s of helium, crystal only.
Soldering conditions	See MAX reflow profile below

MAX Reflow Profile



**FREQUENCY
 CONTROLS, INC.**

357 Beloit Street, P.O. Box 457, Burlington, WI 53105-0457 U.S.A. Phone 262/763-3591 FAX 262/763-2881

Email: nelsales@nelfc.com www.nelfc.com

AB-X29NXXX Series

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Operating Temperature Range	To	-40 to +85	°C
Storage Temperature Range	Tst	-50 to +90	°C
Supply Voltage	Vcc	-0.5 to 5.5	V
Enable/Disable Voltage	Ven/dis	0 to Vcc	V

Electrical Parameters

Parameter	Symb	Conditions, Note	MIN	TYP	MAX	Unit
Nominal Frequency	Fo		200		1,000	MHz
Supply Voltage	Vcc	Code 0 Code A	4.75 3.135	5.0 3.3	5.25 3.465	V
Supply current	Icc			60	80	mA
Output Logic Type				PECL/ LVPECL		
Load		Output to Vcc-2V, or Thevenin Equivalent		50		Ohm
Output Levels	Voh Vol	overall	Vcc-1.025 Vcc-1.620			V
Duty Cycle (Symmetry)		At 50% of output voltage swing	45/55	50/50	55/45	%
Rise/Fall Time	Tr/Tf	20 to 80, 80 to 20 %		0.5	0.7	ns
Jitter	Integrated	J	Integrated from Phase Noise, 12 KHz to 20 MHz , RMS 100Hz to 80KHz,RMS 50 KHz to 80 MHz	0.1	0.2	ps
					1.0	ps
				0.3		ps
	Wavecrest characterized		Random period,	2.5		ps
			Accumul., pk-to-pk	25		ps
			Determin.	1		ps
Phase Noise	f(Δf)	622.080MHz APR 50 ppm or less	@ 10 Hz @100 Hz @1 KHz @10KHz @100KHz @>1MHz	-60 -90 -118 -135 -140 -145	-55 -85 -113 -130 -135 -140	dBc/Hz
Sub-harmonics		At 622.08 MHz		-50	-46	dBc
Frequency Stability	ΔF/F	Overall, including initial calibration, temperature, aging 10 years, shock and vibration			From ±20, see table for part number	ppm
Enable		Pin 2 = Low, 0 to Vcc- 1.62 V	Enabled			V
Disable		Pin 2 = High, Vcc-1.025 V to Vcc	Disabled, Pin4 = Logic "1", Pin5 = Logic "0"			V

