

BLS101SYC-28V-P SUPER BRIGHT YELLOW


### Features

- BUILT-IN CURRENT LIMITING RESISTOR FOR DIRECT APPLICATION OF DIFFERENT ACROSS CURRENT.
- LONG LIFE.
- LOW CURRENT, POWER SAVINGS.
- LOW MAINTENANCE.
- DIFFERENT COLOR AVAILABLE.
- SOLID STATE, HIGH VIBRATION RESISTANT.
- 28V INTERNAL RESISTOR.

### Description

The Super Bright Yellow source color devices are made with DH InGaAlP on GaAs substrate Light Emitting Diode.

### Package Dimensions



#### Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.25(0.01)$  unless otherwise noted.
3. Specifications are subject to change without notice.

## Selection Guide

| Part No.        | Dice                          | Lens Type   | Iv (mcd)<br>V=28V |      | Viewing<br>Angle |
|-----------------|-------------------------------|-------------|-------------------|------|------------------|
|                 |                               |             | Min.              | Typ. | 2θ1/2            |
| BLS101SYC-28V-P | SUPER BRIGHT YELLOW (InGaAlP) | WATER CLEAR | 280               | 350  | 20°              |

Note:


1. θ1/2 is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.

## Electrical / Optical Characteristics at T<sub>A</sub>=25°C

| Symbol            | Parameter                | Device              | Typ. | Max. | Units | Test Conditions     |
|-------------------|--------------------------|---------------------|------|------|-------|---------------------|
| λ <sub>peak</sub> | Peak Wavelength          | Super Bright Yellow | 590  |      | nm    | V <sub>F</sub> =28V |
| λ <sub>D</sub>    | Dominate Wavelength      | Super Bright Yellow | 588  |      | nm    | V <sub>F</sub> =28V |
| Δλ <sub>1/2</sub> | Spectral Line Half-width | Super Bright Yellow | 28   |      | nm    | V <sub>F</sub> =28V |
| I <sub>F</sub>    | Forward Current          | Super Bright Yellow | 11.5 |      | mA    | V <sub>F</sub> =28V |
| I <sub>R</sub>    | Reverse Current          | Super Bright Yellow |      | 10   | μA    | V <sub>R</sub> = 5V |

## Absolute Maximum Ratings at T<sub>A</sub>=25°C

| Parameter             | Super Bright Yellow | Units |
|-----------------------|---------------------|-------|
| Power dissipation     | 400                 | mW    |
| Forward Voltage       | 30                  | V     |
| Reverse Voltage       | 5                   | V     |
| Operating Temperature | -40°C To +70°C      |       |
| Storage Temperature   | -40°C To +85°C      |       |



## Super Bright Yellow BLS101SYC-28V-P

