

### Features

- DC to 4 GHz
- Flanged model
- Low VSWR

### Applications

- High power RF transmission

## CHF5225CBF Series 60 W Power RF Flanged Chip Termination


### General Specifications

Substrate .....Beo  
 Resistive Film.....Thick Film  
 Tab .....Ag  
 Cover Substrate.....AL203  
 Mounting Flange .....Cu plated with Ni  
 Resistance.....50 Ω  
 Tolerance.....±5 %  
 Packaging .....100 pcs./tray


### Absolute Ratings

Power.....60 W  
 Frequency .....4.0 GHz  
 VSWR .....1.2 Maximum

### Characteristic Curve



### Product Dimensions



### How To Order

**CHF 5225 C B F 500 L**

Model \_\_\_\_\_  
 Size \_\_\_\_\_  
 Version \_\_\_\_\_  
 Substrate \_\_\_\_\_  
 Mount \_\_\_\_\_  
     F = Flange  
 Value \_\_\_\_\_  
     500 = 50 Ohm  
 Function \_\_\_\_\_  
     L = Termination



*Reliable Electronic Solutions*

**Asia-Pacific:**

Tel: +886-2 2562-4117  
 Fax: +886-2 2562-4116

**Europe:**

Tel: +41-41 768 5555  
 Fax: +41-41 768 5510

**The Americas:**

Tel: +1-951 781-5500  
 Fax: +1-951 781-5700

**www.bourns.com**

\*RoHS Directive 2002/95/EC Jan 27 2003, including Annex  
 Specifications are subject to change without notice.  
 Customers should verify actual device performance in their specific applications.