



TO-92 Encapsulate Three-terminal voltage regulator

CJ79L08 Three-terminal negative voltage regulator


FEATURES

Maximum Output current

I_{OM} : 0.1A

Output voltage

V_o : -8 V



ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies unless otherwise specified)


Parameter	Symbol	Value	Units
Input Voltage	V_i	-30	V
Operating Junction Temperature Range	T_{OPR}	0—+125	
Storage Temperature Range	T_{STG}	-55—+150	

ELECTRICAL CHARACTERISTICS


($V_i=-14V, I_o=40mA, 0 < T_j < 125$, $C_1=0.33 \mu F, C_o=0.1 \mu F$, unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Output voltage	V_o	$V_{IN}=-14V, I_o=40mA$	-7.7	-8.0	-8.3	V
Line Regulation	V_o-V_{IN}	$V_{IN}=-10.5\sim-23V, I_o=40mA$		42	200	mV
Load Regulation	V_o-I_o	$V_{IN}=-14V, I_o=1\sim100mA$		30	100	mV
Quiescent Current	I_Q	$V_{IN}=-14V, I_o=40mA$			6.0	mA
Ripple Rejection	RR	$V_{IN}=-11V\sim-21V, I_o=40mA, e_{iN}=1V_{P-P}, f=120Hz$	37	46		dB
Output Noise Voltage	V_{NO}	$V_{IN}=-14V, f=10Hz\sim100KH, I_o=40mA$		54		μV

TYPICAL APPLICATION



TO-92 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	3.300	3.700	0.130	0.146
A1	1.100	1.400	0.043	0.055
b	0.380	0.550	0.015	0.022
c	0.360	0.510	0.014	0.020
D	4.400	4.700	0.173	0.185
D1	3.430		0.135	
E	4.300	4.700	0.169	0.185
e	1.270TYP		0.050TYP	
e1	2.440	2.640	0.096	0.104
L	14.100	14.500	0.555	0.571
Ö		1.600		0.063
\downarrow	0.000	0.380	0.000	0.015