



NPN AF LOW NOISE
SILICON PLANAR EPITAXIAL TRANSISTOR

MICRO ELECTRONICS

GENERAL DESCRIPTION

The CL146 is a NPN silicon planar epitaxial transistor in plastic package designed for hearing aids, watches, paging systems and other equipment where small size is of paramount importance.

T0-92B



ECB

ABSOLUTE MAXIMUM RATINGS

Collector-Base Voltage
Collector-Emitter Voltage
Emitter-Base Voltage
Collector Current
Total Power Dissipation at $T_A \leq 45^\circ\text{C}$
Junction Temperature
Storage Temperature Range

V_{CBO}
 V_{CEO}
 V_{EBO}
 I_C
 P_{tot}
 T_j
 T_{stg}

20V
20V
4V
50mA
50mW
125°C
-65°C to +125°C

THERMAL RESISTANCE

Junction to Ambient

θ_{ja}

1.6°C/mW

ELECTRICAL CHARACTERISTICS AT $T_A = 25^\circ\text{C}$

PARAMETER	SYMBOL	146R			146Y			146G			UNIT	TEST CONDITIONS
		MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX		
Collector-Base Cutoff Current	I_{CBO}			100			100			100	nA	$V_{CB}=20V$ $I_E=0$
Collector-Emitter Knee Voltage	V_{CEK}		200			200			200		mV	$I_C=2mA$ I_B -value for which $I_C=2mA$ and $V_{CE}=1V$
Base-Emitter Voltage	V_{BE}		570			570			570		mV	$V_{CE}=0.5V$ $I_C=0.2mA$
Base-Emitter Voltage	V_{BE}		630			630			630		mV	$V_{CE}=1V$ $I_C=2mA$
DC Current Gain	HFE	80	120	200	140	220	350	280	380	550		$V_{CE}=0.5V$ $I_C=0.2mA$
DC Current Gain	HFE	100			140			280				$V_{CE}=1V$ $I_C=2mA$
Noise Figure	NF		1.5			1.5	4		1.5		dB	$V_{CE}=5V$ $I_C=0.2mA$ $R_g=2K\Omega$ $f=30Hz-15KHz$
Transition Frequency	f_T		80			110			150		MHz	$V_{CE}=5V$ $I_C=2mA$
Collector Capacitance	C_{cb}		2.5			2.5			2.5		pF	$V_{CB}=5V$ $I_E=0$ $f=1MHz$

TYPICAL h-PARAMETERS AT $V_{CE}=0.5V$, $I_C=0.2mA$, $f=1KHz$

PARAMETER	SYMBOL	146R	146Y	146G	UNIT
Input Impedance	h_{ie}	20	30	45	$K\Omega$
Reverse Voltage Transfer Ratio	h_{re}	15	25	40	$\times 10^{-4}$
Small Signal Current Gain	h_{fe}	130	240	400	
Output Admittance	h_{oe}	15	20	35	μS

MICRO ELECTRONICS LTD.

38 HUNG TO ROAD, KWUN TONG, HONG KONG. TELEX 43510
KWUN TONG P. O. BOX 6477 CABLE ADDRESS "MICROTRON"
TELEPHONE: 3-430181-8, 3-893363, 9-892423, 3-898221
FAX: 2 410221