


### Features

- Glass Passivated Junction
- High Current Capability
- Low Forward Voltage Drop
- Low Leakage Current
- Lead Free Finish/RoHS Compliant Version (Note 2)**



### Mechanical Data

- Case: MELF
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Terminals: Solderable per MIL-STD-202, Method 208 **(e3)**
- Lead Free Plating (Matte Tin Finish).
- Polarity: Cathode Band
- Marking: Cathode Band Only
- Approximate Weight: 0.25 grams

MELF		
Dim	Min	Max
A	4.80	5.20
B	2.60	2.64
C	0.55 Nominal	
All Dimensions in mm		

### Maximum Ratings and Electrical Characteristics @ T<sub>A</sub> = 25 C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

Characteristic	Symbol	DL 4001	DL 4002	DL 4003	DL 4004	DL 4005	DL 4006	DL 4007	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V <sub>RRM</sub> V <sub>RWM</sub> V <sub>R</sub>	50	100	200	400	600	800	1000	V
RMS Reverse Voltage	V <sub>R(RMS)</sub>	35	71	141	283	424	566	707	V
Average Forward Rectified Current @ T <sub>T</sub> = 75 C	I <sub>O</sub>	1.0							A
Peak Forward Surge Current 8.3ms single half sine-wave Superimposed on Rated Load	I <sub>FSM</sub>	30							A
Maximum Forward Voltage @ I <sub>F</sub> = 1.0A	V <sub>FM</sub>	1.1							V
Maximum DC Reverse Current @ T <sub>A</sub> = 25 C @ Rated DC Blocking Voltage @ T <sub>A</sub> = 100 C	I <sub>RM</sub>	5.0 50							A
Typical Thermal Resistance, Junction to Ambient Air	R <sub>JA</sub>	50							C/W
Typical Total Capacitance (Note 1)	C <sub>T</sub>	15							pF
Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to +150							C

- Notes:
1. Measured at 1.0MHz and applied reverse voltage of 4.0 volts.
  2. RoHS revision 13.2.2003. Glass and High Temperature Solder Exemptions Applied, see *EU Directive Annex Notes 5 and 7*.




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Typical Total Capacitance vs. Reverse Voltage




Fig. 4 Max Non-Repetitive Peak Forward Surge Current

**Ordering Information**

Device	Packaging	Shipping
DL4001-13-F	MELF	5,000/Tape & Reel
DL4002-13-F	MELF	5,000/Tape & Reel
DL4003-13-F	MELF	5,000/Tape & Reel
DL4004-13-F	MELF	5,000/Tape & Reel
DL4005-13-F	MELF	5,000/Tape & Reel
DL4006-13-F	MELF	5,000/Tape & Reel
DL4007-13-F	MELF	5,000/Tape & Reel

**IMPORTANT NOTICE**

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

**LIFE SUPPORT**

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.