



## Specifications

**GVXO-32L: +3.3V supply**

**GVXO-32S: +5.0V supply**

Parameters	Variant		Option Codes
	L	S	
<b>Frequency range:</b> 52.0 ~ 160MHz	■	■	
<b>Voltage control (<math>V_{CTL}</math>):</b> +1.65V $\pm$ 1.5V, 10% linearity +2.5V $\pm$ 2.0V, 10% linearity	■	■	
<b>Frequency pullability:</b> $\pm$ 80ppm min $\pm$ 100ppm min Other	■	■	specify
<b>Frequency stability*:</b> $\pm$ 50ppm max Other	■	■	specify
<b>Operating temperature range:</b> -10 to +70°C	■	■	
<b>Storage temperature range:</b> -40 to +85°C	■	■	
<b>Supply voltage (<math>V_{DD}</math>):</b> +3.3V ( $\pm$ 5%) +5.0V ( $\pm$ 5%)	■	■	
<b>Supply current (mA max):</b>	60	80	
<b>Driving ability:</b> 15pF CMOS	■	■	
<b>Logic levels:</b> '0' level = 10% $V_{DD}$ max '1' level = 90% $V_{DD}$ min	■	■	
<b>Waveform symmetry:</b> 40:60 max @ 50% $V_{DD}$	■	■	
<b>Start up time:</b> 10ms max	■	■	
<b>Rise / fall time:</b> 3ns max (20% ~ 80% $V_{DD}$ )	■	■	
<b>Enable / disable function:</b> Tristate (control via pad 2) None (pad 2 NC)	■	■	N
<b>Soldering condition:</b> Reflow, 240°C max	■	■	

■ Standard. □ Optional - Please specify required code(s) when ordering

\* Frequency stability is inclusive of calibration @ 25°C, operating temperature range, supply voltage change, load change and ageing, with  $V_{CTL} = 50\% V_{DD}$

## Features

- ▶ CMOS compatible output
- ▶ Low jitter and fast rise / fall
- ▶ Popular telecomms package layout
- ▶ Enable / disable tristate function

## Enable / Disable Function

Input (pad 2)	Output (pad 4)
Open '1' level $V_{IH}$ '0' level $V_{IL}$	Active Active High Impedance

## Ordering Information

Product name + variant + option codes (if any) + frequency  
eg: **GVXO-32L 77.760MHz** 3.3V,  $\pm$ 80ppm pullability, with E/D

**GVXO-32S/N 155.520MHz** 5.0V,  $\pm$ 100ppm pullability, no E/D

Option code X (eg GVXO-32S/X) denotes a combination of values not listed above.

- ◆ Available on T&R - 1k pcs per reel. Refer to our website for details.
- ◆ Some combinations of stability/pullability are not available