
HM514170C Series

HM51S4170C Series

262,144-word \times 16-bit Dynamic Random Access Memory

HITACHI

Rev. 1.0
Jul. 21, 1995

Description

The Hitachi HM51(S)4170C are CMOS dynamic RAM organized as 262,144-word \times 16-bit. HM51(S)4170C have realized higher density, higher performance and various functions by employing 0.8 μ m CMOS process technology and some new CMOS circuit design technologies. The HM51(S)4170C offer fast page mode as a high speed access mode. Multiplexed address input permits the HM51(S)4170C to be packaged in standard 400-mil 40-pin plastic SOJ and standard 400-mil 44-pin plastic TSOPII. Internal refresh timer enables HM51S4170C self refresh operation.

Features


- Single 5 V ($\pm 10\%$)
- High speed
 - Access time: 70 ns/80 ns (max)
- Low power dissipation
 - Active mode: 660 mW/578 mW (max)
 - Standby mode: 11 mW (max)
1.1 mW (max) (L-version)
- Fast page mode capability
- 1024 refresh cycles: 16 ms
128 ms (L-version)
- 2 $\overline{\text{WE}}$ -byte control
- 2 variations of refresh
 - $\overline{\text{RAS}}$ -only refresh
 - $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh
- Battery backup operation (L-version)
- Self refresh operation (HM51S4170C)

HM514170C, HM51S4170C Series


Ordering Information

| Type No. | Access Time | Package |
|------------------------------------|----------------|---|
| HM514170CJ-7 HM514170CJ-8 | 70 ns 80 ns | 400-mil 40-pin plastic SOJ (CP-40DA) |
| HM514170CLJ-7 HM514170CLJ-8 | 70 ns 80 ns | |
| HM51S4170CJ-7 HM51S4170CJ-8 | 70 ns 80 ns | |
| HM51S4170CLJ-7 HM51S4170CLJ-8 | 70 ns 80 ns | |
| HM514170CTT-7 HM514170CTT-8 | 70 ns 80 ns | 400-mil 44-pin plastic TSOPII (TTP-44/40DB) |
| HM514170CLTT-7 HM514170CLTT-8 | 70 ns 80 ns | |
| HM51S4170CTT-7 HM51S4170CTT-8 | 70 ns 80 ns | |
| HM51S4170CLTT-7 HM51S4170CLTT-8 | 70 ns 80 ns | |

Pin Arrangement



(Top view)




(Top view)

Pin Description

| Pin Name | Function |
|---|---|
| A0 – A9 | Address input – Row address A0 – A9 – Column address A0 – A7 – Refresh address A0 – A9 |
| I/O0 – I/O15 | Data-in/data-out |
| RAS | Row address strobe |
| CAS | Column address strobe |
| $\overline{\text{UWE}}$ / $\overline{\text{LWE}}$ | Read/write enable |
| OE | Output enable |
| V _{CC} | Power (+5 V) |
| V _{SS} | Ground |
| NC | No connection |

HM514170C, HM51S4170C Series

Block Diagram



Operation Mode

The HM51(S)4170C series has the following 11 operation modes.

1. Read cycle
2. Early write cycle
3. Delayed write cycle
4. Read-modify-write cycle
5. $\overline{\text{RAS}}$ -only refresh cycle
6. $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh cycle
7. Self refresh cycle (HM51S4170C)
8. Fast page mode read cycle
9. Fast page mode early write cycle
10. Fast page mode delayed write cycle
11. Fast page mode read-modify-write cycle

| Inputs | | | | | |
|-------------------------|-------------------------|-------------------------|-------------------------|-----------|---|
| $\overline{\text{RAS}}$ | $\overline{\text{CAS}}$ | $\overline{\text{UWE}}$ | $\overline{\text{LWE}}$ | Output | Operation |
| H | H | D | D | Open | Standby |
| H | L | H | H | Valid | Standby |
| L | L | H | H | Valid | Read cycle |
| L | L | L ² | L ² | Open | Early write cycle |
| L | L | L ² | L ² | Undefined | Delayed write cycle |
| L | L | H to L | H to L | Valid | Read-modify-write cycle |
| L | H | D | D | Open | $\overline{\text{RAS}}$ -only refresh cycle |
| H to L | L | D | D | Open | $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh cycle Self refresh cycle (HM51S4170C) |
| L | H to L | H | H | Valid | Fast page mode read cycle |
| L | H to L | L ² | L ² | Open | Fast page mode early write cycle |
| L | H to L | L ² | L ² | Undefined | Fast page mode delayed write cycle |
| L | H to L | H to L | H to L | Valid | Fast page mode read modify-write cycle |

Notes: 1. H: High (inactive) L: Low (active) D: H or L

2. $t_{\text{wCS}} \geq 0$ ns Early write cycle

$t_{\text{wCS}} < 0$ ns Delay write cycle

3. Mode is determined by the OR function of the $\overline{\text{UWE}}$ and $\overline{\text{LWE}}$. (Mode is set by the earliest of $\overline{\text{UWE}}$ and $\overline{\text{LWE}}$ active edge and reset by the latest of $\overline{\text{UWE}}$ and $\overline{\text{LWE}}$ inactive edge.) However write OPERATION and output HIZ control are done independently by each $\overline{\text{UWE}}$, $\overline{\text{LWE}}$.

HM514170C, HM51S4170C Series

Absolute Maximum Ratings

| Parameter | Symbol | Value | Unit |
|---|-----------|--------------|------|
| Voltage on any pin relative to V_{SS} | V_T | -1.0 to +7.0 | V |
| Supply voltage relative to V_{SS} | V_{CC} | -1.0 to +7.0 | V |
| Short circuit output current | I_{out} | 50 | mA |
| Power dissipation | P_T | 1.0 | W |
| Operating temperature | T_{opr} | 0 to +70 | °C |
| Storage temperature | T_{stg} | -55 to +125 | °C |

Recommended DC Operating Conditions ($T_a = 0$ to $+70^\circ\text{C}$)

| Parameter | Symbol | Min | Typ | Max | Unit | Note |
|--------------------|----------|------|-----|-----|------|------|
| Supply voltage | V_{SS} | 0 | 0 | 0 | V | 2 |
| | V_{CC} | 4.5 | 5.0 | 5.5 | V | 1, 2 |
| Input high voltage | V_{IH} | 2.4 | — | 6.5 | V | 1 |
| Input low voltage | V_{IL} | -1.0 | — | 0.8 | V | 1 |

Notes: 1. All voltage referred to V_{SS}

2. The supply voltage with all V_{CC} pins must be on the same level.

The supply voltage with all V_{SS} pins must be on the same level.

DC Characteristics ($T_a = 0$ to $+70^\circ\text{C}$, $V_{CC} = 5\text{ V} \pm 10\%$, $V_{SS} = 0\text{ V}$)

| | | HM514170C, HM51S4170C | | | | | |
|---|-----------|-----------------------|-----|-----|-----|---------------|--|
| | | -7 | | -8 | | | |
| Parameter | Symbol | Min | Max | Min | Max | Unit | Test Conditions |
| Operating current ^{*1,*2} | I_{CC1} | — | 120 | — | 105 | mA | $\overline{\text{RAS}}$, $\overline{\text{CAS}}$ cycling $t_{RC} = \text{min}$ |
| Standby current | I_{CC2} | — | 2 | — | 2 | mA | TTL interface $\overline{\text{RAS}}$, $\overline{\text{CAS}} = V_{IH}$ Dout = High-Z |
| | | — | 1 | — | 1 | | CMOS interface $\overline{\text{RAS}}$, $\overline{\text{CAS}}$, $\overline{\text{UWE}}$, $\overline{\text{LWE}}$, $\overline{\text{OE}} \geq V_{CC} - 0.2\text{ V}$ Dout = High-Z |
| Standby current (L-version) | I_{CC2} | — | 200 | — | 200 | μA | CMOS interface $\overline{\text{RAS}}$, $\overline{\text{CAS}}$, $\overline{\text{OE}}$, $\overline{\text{UWE}}$, $\overline{\text{LWE}} \geq V_{CC} - 0.2\text{ V}$ Dout = High |
| $\overline{\text{RAS}}$ -only refresh current ^{*2} | I_{CC3} | — | 120 | — | 100 | mA | $t_{RC} = \text{min}$ |

HM514170C, HM51S4170C Series

DC Characteristics (Ta = 0 to +70°C, V_{CC} = 5 V ± 10%, V_{SS} = 0 V) (cont)

| | | HM514170C, HM51S4170C | | | | | |
|--|-------------------|-----------------------|-----------------|-----|-----------------|------|---|
| | | -7 | | -8 | | | |
| Parameter | Symbol | Min | Max | Min | Max | Unit | Test Conditions |
| Standby current ^{*1} | I _{CC5} | — | 5 | — | 5 | mA | $\overline{\text{RAS}} = V_{\text{IH}}, \overline{\text{CAS}} = V_{\text{IL}}$ Dout = enable |
| $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh current ^{*2} | I _{CC6} | — | 120 | — | 100 | mA | t _{RC} = min |
| Fast page mode current ^{*1, *3} | I _{CC7} | — | 130 | — | 120 | mA | t _{PC} = min |
| Battery backup current ^{*4} (Standby with CBR refresh) (L-version) | I _{CC10} | — | 300 | — | 300 | μA | Standby: CMOS interface Dout = High-Z CBR refresh: t _{RC} = 125 μs t _{RAS} ≤ 1 μs, $\overline{\text{CAS}} = V_{\text{IL}}$ $\overline{\text{UWE}}, \overline{\text{LWE}}, \overline{\text{OE}} = V_{\text{IH}}$ |
| Self-refresh mode current (HM51S4170C) | I _{CC11} | — | 1 | — | 1 | mA | CMOS interface $\overline{\text{RAS}}, \overline{\text{CAS}} \leq 0.2 \text{ V}$, Dout = High-Z |
| Self-refresh mode current (HM51S4170CL) | I _{CC11} | — | 200 | — | 200 | μA | CMOS interface $\overline{\text{RAS}}, \overline{\text{CAS}} \leq 0.2 \text{ V}$, Dout = High-Z |
| Input leakage current | I _{LI} | -10 | 10 | -10 | 10 | μA | 0 V ≤ Vin ≤ 6.5 V |
| Output leakage current | I _{LO} | -10 | 10 | -10 | 10 | μA | 0 V ≤ Vout ≤ 6.5 V Dout = disable |
| Output high voltage | V _{OH} | 2.4 | V _{CC} | 2.4 | V _{CC} | V | High Iout = -5.0 mA |
| Output low voltage | V _{OL} | 0 | 0.4 | 0 | 0.4 | V | Low Iout = 4.2 mA |

- Notes: 1. I_{CC} depends on output load condition when the device is selected. I_{CC} max is specified at the output open condition.
 2. Address can be changed once or less while $\overline{\text{RAS}} = V_{\text{IL}}$.
 3. Address can be changed once or less while $\overline{\text{CAS}} = V_{\text{IH}}$.
 4. $V_{\text{IH}} \geq V_{\text{CC}} - 0.2 \text{ V}$, $0 \leq V_{\text{IL}} \leq 0.2 \text{ V}$, Address can be changed once or less while $\overline{\text{RAS}} = V_{\text{IL}}$.
 5. All the V_{CC} pins shall be supplied with the same voltage. And all the V_{SS} pins shall be supplied with the same voltage.

Capacitance (Ta = 25°C, V_{CC} = 5 V ± 10%)

| Parameter | Symbol | Typ | Max | Unit | Notes |
|--|------------------|-----|-----|------|-------|
| Input capacitance (Address) | C _{I1} | — | 5 | pF | 1 |
| Input capacitance (Clocks) | C _{I2} | — | 7 | pF | 1 |
| Output capacitance (Data-in, Data-out) | C _{I/O} | — | 10 | pF | 1, 2 |

- Notes: 1. Capacitance measured with Boonton Meter or effective capacitance measuring method.
 2. $\overline{\text{CAS}} = V_{\text{IH}}$ to disable Dout.

HM514170C, HM51S4170C Series

AC Characteristics ($T_a = 0$ to $+70^\circ\text{C}$, $V_{CC} = 5\text{ V} \pm 10\%$, $V_{SS} = 0\text{ V}$)^{*1, *14, *15, *17, *18}

Test Conditions

Read, Write, Read-Modify-Write and Refresh Cycles (Common Parameters)

- Input rise and fall time: 5 ns
- Input timing reference levels: 0.8 V, 2.4 V
- Input levels: 0 V, 3 V
- Output load: 2 TTL gate + C_L (100 pF) (Including scope and jig)

| Parameter | Symbol | HM514170C, HM51S4170C | | | | Unit | Notes |
|---|-----------|-----------------------|-------|-----|-------|------|-------|
| | | -7 | | -8 | | | |
| | | Min | Max | Min | Max | | |
| Random read or write cycle time | t_{RC} | 130 | — | 150 | — | ns | |
| $\overline{\text{RAS}}$ precharge time | t_{RP} | 50 | — | 60 | — | ns | |
| $\overline{\text{RAS}}$ pulse width | t_{RAS} | 70 | 10000 | 80 | 10000 | ns | |
| $\overline{\text{CAS}}$ pulse width | t_{CAS} | 20 | 10000 | 20 | 10000 | ns | 22 |
| Row address setup time | t_{ASR} | 0 | — | 0 | — | ns | |
| Row address hold time | t_{RAH} | 10 | — | 10 | — | ns | |
| Column address setup time | t_{ASC} | 0 | — | 0 | — | ns | |
| Column address hold time | t_{CAH} | 15 | — | 15 | — | ns | |
| $\overline{\text{RAS}}$ to $\overline{\text{CAS}}$ delay time | t_{RCD} | 20 | 50 | 20 | 60 | ns | 8 |
| $\overline{\text{RAS}}$ to column address delay time | t_{RAD} | 15 | 35 | 15 | 40 | ns | 9 |
| $\overline{\text{RAS}}$ hold time | t_{RSH} | 20 | — | 20 | — | ns | |
| $\overline{\text{CAS}}$ hold time | t_{CSH} | 70 | — | 80 | — | ns | |
| $\overline{\text{CAS}}$ to $\overline{\text{RAS}}$ precharge time | t_{CRP} | 15 | — | 15 | — | ns | 23 |
| $\overline{\text{OE}}$ to Din delay time | t_{ODD} | 20 | — | 20 | — | ns | |
| $\overline{\text{OE}}$ delay time from Din | t_{DZO} | 0 | — | 0 | — | ns | |
| $\overline{\text{CAS}}$ setup time from Din | t_{DZC} | 0 | — | 0 | — | ns | |
| Transition time (rise and fall) | t_T | 3 | 50 | 3 | 50 | ns | 7 |
| Refresh period | t_{REF} | — | 16 | — | 16 | ms | |
| Refresh period (L-version) | t_{REF} | — | 128 | — | 128 | ms | |

HM514170C, HM51S4170C Series

Read Cycle

| Parameter | Symbol | HM514170C, HM51S4170C | | | | Unit | Notes |
|---|-------------------|-----------------------|-----|-----|-----|------|----------|
| | | -7 | | -8 | | | |
| | | Min | Max | Min | Max | | |
| Access time from $\overline{\text{RAS}}$ | t_{RAC} | — | 70 | — | 80 | ns | 2, 3 |
| Access time from $\overline{\text{CAS}}$ | t_{CAC} | — | 20 | — | 20 | ns | 3, 4, 13 |
| Access time from address | t_{AA} | — | 35 | — | 40 | ns | 3, 5, 13 |
| Access time from $\overline{\text{OE}}$ | t_{OAC} | — | 20 | — | 20 | ns | 22 |
| Read command setup time | t_{RCS} | 0 | — | 0 | — | ns | 20 |
| Read command hold time to $\overline{\text{CAS}}$ | t_{RCH} | 0 | — | 0 | — | ns | 16, 19 |
| Read command hold time to $\overline{\text{RAS}}$ | t_{RRH} | 0 | — | 0 | — | ns | 16 |
| Column address to $\overline{\text{RAS}}$ lead time | t_{RAL} | 35 | — | 40 | — | ns | |
| Output buffer turn-off time | t_{OFF1} | 0 | 15 | 0 | 15 | ns | 6 |
| Output buffer turn-off to $\overline{\text{OE}}$ | t_{OFF2} | 0 | 15 | 0 | 15 | ns | 6 |
| $\overline{\text{CAS}}$ to Din delay time | t_{CDD} | 15 | — | 15 | — | ns | |

Write Cycle

| Parameter | Symbol | HM514170C, HM51S4170C | | | | Unit | Notes |
|--|------------------|-----------------------|-----|-----|-----|------|--------|
| | | -7 | | -8 | | | |
| | | Min | Max | Min | Max | | |
| Write command setup time | t_{WCS} | 0 | — | 0 | — | ns | 10, 19 |
| Write command hold time | t_{WCH} | 15 | — | 15 | — | ns | 20 |
| Write command pulse width | t_{WP} | 10 | — | 10 | — | ns | 21 |
| Write command to $\overline{\text{RAS}}$ lead time | t_{RWL} | 20 | — | 20 | — | ns | 21 |
| Write command to $\overline{\text{CAS}}$ lead time | t_{CWL} | 20 | — | 20 | — | ns | 21 |
| Data-in setup time | t_{DS} | 0 | — | 0 | — | ns | 11, 21 |
| Data-in hold time | t_{DH} | 15 | — | 15 | — | ns | 11, 21 |
| $\overline{\text{CAS}}$ to $\overline{\text{OE}}$ delay time | t_{COD} | — | 0 | — | 0 | ns | 22 |

HM514170C, HM51S4170C Series

Read-Modify-Write Cycle

| Parameter | Symbol | HM514170C, HM51S4170C | | | | Unit | Notes |
|--|-----------|-----------------------|-----|-----|-----|------|--------|
| | | -7 | | -8 | | | |
| | | Min | Max | Min | Max | | |
| Read-modify-write cycle time | t_{RWC} | 180 | — | 200 | — | ns | |
| \overline{RAS} to \overline{WE} delay time | t_{RWD} | 95 | — | 105 | — | ns | 10, 19 |
| \overline{CAS} to \overline{WE} delay time | t_{CWD} | 45 | — | 45 | — | ns | 10, 19 |
| Column address to \overline{WE} delay time | t_{AWD} | 60 | — | 65 | — | ns | 10, 19 |
| \overline{OE} hold time from \overline{WE} | t_{OEH} | 20 | — | 20 | — | ns | 21 |

Refresh Cycle

| Parameter | Symbol | HM514170C, HM51S4170C | | | | Unit | Notes |
|--|-----------|-----------------------|-----|-----|-----|------|-------|
| | | -7 | | -8 | | | |
| | | Min | Max | Min | Max | | |
| \overline{CAS} setup time (CBR refresh cycle) | t_{CSR} | 10 | — | 10 | — | ns | 19 |
| \overline{CAS} hold time (CBR refresh cycle) | t_{CHR} | 10 | — | 10 | — | ns | 20 |
| \overline{RAS} precharge to \overline{CAS} hold time | t_{RPC} | 10 | — | 10 | — | ns | 19 |
| \overline{CAS} precharge time in normal mode | t_{CPN} | 10 | — | 10 | — | ns | |

Fast Page Mode Cycle



| Parameter | Symbol | HM514170C, HM51S4170C | | | | Unit | Notes |
|---|------------|-----------------------|--------|-----|--------|------|-------|
| | | -7 | | -8 | | | |
| | | Min | Max | Min | Max | | |
| Fast page mode cycle time | t_{PC} | 45 | — | 50 | — | ns | |
| Fast page mode \overline{CAS} precharge time | t_{CP} | 10 | — | 10 | — | ns | |
| Fast page mode \overline{RAS} pulse width | t_{RASC} | — | 100000 | — | 100000 | ns | 12 |
| Access time from \overline{CAS} precharge | t_{ACP} | — | 40 | — | 45 | ns | 3, 13 |
| RAS hold time from \overline{CAS} precharge | t_{RHCP} | 40 | — | 45 | — | ns | |
| Fast page mode read-modify-write cycle \overline{CAS} precharge to \overline{UWE} , \overline{LWE} delay time | t_{CPW} | 65 | — | 70 | — | ns | 21 |
| Fast page mode read-modify-write cycle time | t_{PCM} | 95 | — | 100 | — | ns | |

Self refresh Mode

| Parameter | Symbol | HM51S4170C | | | | Unit | Notes |
|---|-------------------|------------|-----|-----|-----|---------------|------------|
| | | -7 | | -8 | | | |
| | | Min | Max | Min | Max | | |
| $\overline{\text{RAS}}$ pulse width (self refresh) | t_{RASS} | 100 | — | 100 | — | μs | 23, 24, 25 |
| $\overline{\text{RAS}}$ precharge time (self refresh) | t_{RPS} | 130 | — | 150 | — | ns | |
| $\overline{\text{CAS}}$ hold time (self refresh) | t_{CHS} | -50 | — | -50 | — | ns | |

Notes: 1. AC measurements assume $t_{\tau} = 5 \text{ ns}$.


2. Assumes that $t_{\text{RCD}} \leq t_{\text{RCD}} (\text{max})$ and $t_{\text{RAD}} \leq t_{\text{RAD}} (\text{max})$. If t_{RCD} or t_{RAD} is greater than the maximum recommended value shown in this table, t_{RAC} exceeds the value shown.
3. Measured with a load circuit equivalent to 2 TTL loads and 100 pF.
4. Assumes that $t_{\text{RCD}} \geq t_{\text{RCD}} (\text{max})$ and $t_{\text{RAD}} \leq t_{\text{RAD}} (\text{max})$.
5. Assumes that $t_{\text{RCD}} \leq t_{\text{RCD}} (\text{max})$ and $t_{\text{RAD}} \geq t_{\text{RAD}} (\text{max})$.
6. $t_{\text{OFF}} (\text{max})$ defines the time at which the output achieves the open circuit condition and is not referred to output voltage levels.
7. $V_{\text{IH}} (\text{min})$ and $V_{\text{IL}} (\text{max})$ are reference levels for measuring timing of input signals. Also, transition times are measured between V_{IH} and V_{IL} .
8. Operation with the $t_{\text{RCD}} (\text{max})$ limit insures that $t_{\text{RAC}} (\text{max})$ can be met, $t_{\text{RCD}} (\text{max})$ is specified as a reference point only, if t_{RCD} is greater than the specified $t_{\text{RCD}} (\text{max})$ limit, then access time is controlled exclusively by t_{CAC} .
9. Operation with the $t_{\text{RAD}} (\text{max})$ limit insures that $t_{\text{RAC}} (\text{max})$ can be met, $t_{\text{RAD}} (\text{max})$ is specified as a reference point only, if t_{RAD} is greater than the specified $t_{\text{RAD}} (\text{max})$ limit, then access time is controlled exclusively by t_{AA} .
10. t_{WCS} , t_{RWD} , t_{CWD} and t_{AWD} are not restrictive operating parameters. They are included in the data sheet as electrical characteristics only: if $t_{\text{WCS}} \geq t_{\text{WCS}} (\text{min})$, the cycle is an early write cycle and the data out pin will remain open circuit (high impedance) throughout the entire cycle; if $t_{\text{RWD}} \geq t_{\text{RWD}} (\text{min})$, $t_{\text{CWD}} \geq t_{\text{CWD}} (\text{min})$, $t_{\text{AWD}} \geq t_{\text{AWD}} (\text{min})$ and $t_{\text{CPW}} \geq t_{\text{CPW}} (\text{min})$, the cycle is a read-modify-write and the data output will contain data read from the selected cell; if neither of the above sets of conditions is satisfied, the condition of the data out (at access time) is indeterminate.
11. These parameters are referred to $\overline{\text{CAS}}$ leading edge in an early write cycle and to $\overline{\text{WE}}$ leading edge in a delayed write or a read-modify-write cycle.
12. t_{RASC} defines $\overline{\text{RAS}}$ pulse width in fast page mode cycles.
13. Access time is determined by the longer of t_{AA} or t_{CAC} or t_{ACP} .
14. After power up pause for 100 μs , then DRAM initialization requires a minimum of eight $\overline{\text{RAS}}$ only refresh or eight $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ refresh cycles. If the user will implement $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ timing in their system, then the eight initialization cycles MUST be $\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ cycles
15. In delayed write or read-modify-write cycles, $\overline{\text{OE}}$ must disable output buffer prior to applying data to the device.
16. Either t_{RCH} or t_{RRH} must be satisfied for a read cycle.
17. The supply voltage with all V_{CC} pins must be on the same level. The supply voltage with all V_{SS} pins must be on the same level.
18. A word of data can be written only when $\overline{\text{UWE}}$ and $\overline{\text{LWE}}$ go low at the same time. This implies that early write cycles cannot be combined with delayed write cycles in the same cycles because all data is latched at the fall of the first $\overline{\text{WE}}$. In other words, staggering the $\overline{\text{WE}}$ signals in one cycle is not permitted.
19. t_{RCH} , t_{RRH} , t_{WCS} , t_{RWD} , t_{CWD} and t_{AWD} are determined by the earlier falling edge of $\overline{\text{UWE}}$ and $\overline{\text{LWE}}$.
20. t_{WCH} and t_{RCS} are determined by the later rising edge of $\overline{\text{UWE}}$ or $\overline{\text{LWE}}$.
21. t_{WP} , t_{RWL} , t_{CWL} , t_{OEH} , t_{DS} , t_{DH} and t_{CPW} should be satisfied by both $\overline{\text{UWE}}$ and $\overline{\text{LWE}}$.

22. When output buffers are enabled once, sustain the low impedance state until valid data is obtained. When output buffer is turned on and off within a very short time, generally it causes large V_{CC}/V_{SS} line noise, which causes to degrade $V_{IH}(\min)/V_{IL}(\max)$ level.
23. If you use distributed CBR refresh mode with 15.6 μs interval in normal read/write cycle, CBR refresh should be executed within 15.6 μs immediately after exiting from and before entering into self refresh mode.
24. If you use $\overline{\text{RAS}}$ only refresh or CBR burst refresh mode in normal read/write cycle, 1024 cycles of distributed CBR refresh with 15.6 μs interval should be executed within 16 ms immediately after exiting from and before entering into the self refresh mode.
25. Repetitive self refresh mode without refreshing all memory is not allowed. Once you exit from self refresh mode, all memory cells need to be refreshed before re-entering the self refresh mode again.
26.  H or L (H: $V_{IH}(\min) \leq V_{IN} \leq V_{IH}(\max)$, L: $V_{IL}(\min) \leq V_{IN} \leq V_{IL}(\max)$)
 Invalid Dout


Notes concerning $\overline{2WE}$ control

Please do not separate the $\overline{UWE/LWE}$ operation timing intentionally. However skew between $\overline{UWE/LWE}$ are allowed under the following conditions.

- (1) Each of the $\overline{UWE/LWE}$ should satisfy the timing specifications individually.
- (2) Different operation mode for upper/lower byte is not allowed; such as following.




- (3) Closely separated upper/lower byte control is not allowed. Unless the condition ($t_{CP} \leq t_{UL}$) is satisfied.




HM514170C, HM51S4170C Series

Timing Waveforms ^{*26}

Read Cycle




Early Write Cycle




* \overline{OE} : H or L

HM514170C, HM51S4170C Series

Delayed Write Cycle




Read-Modify-Write Cycle



HM514170C, HM51S4170C Series


$\overline{\text{RAS}}$ -Only Refresh Cycle



* $\overline{\text{UWE}}$, $\overline{\text{LWE}}$ and $\overline{\text{OE}}$: H or L

** Refresh address : A0 – A9 (AX0 – AX9)


CAS-Before-RAS Refresh Cycle



* \overline{UWE} , \overline{LWE} : H or L


** Do not extend $t_{RAS} \geq t_{RAS}(\text{max})$.
 Untested self refresh mode may be activated and loss of data may be resulted.
 (HM514170C)

Fast Page Mode Early Write Cycle




HM514170C, HM51S4170C Series


Fast Page Mode Delayed Write Cycle



Fast Page Mode Read-Modify-Write Cycle



Self Refresh Cycle



* $\overline{\text{UWE}}$, $\overline{\text{LWE}}$ and $\overline{\text{OE}}$: H or L


The low self refresh current is achieved by introducing extremely long internal refresh cycle. Therefore some care needs to be taken on the refresh.

1. Please do not use t_{RASS} timing, $10 \mu\text{s} \leq t_{RASS} \leq 100 \mu\text{s}$. During this period, the device is in transition state from normal operation mode to self refresh mode. If $t_{RASS} \geq 100 \mu\text{s}$, then $\overline{\text{RAS}}$ precharge time should use t_{RPS} instead of t_{RP} .
2. If you use $\overline{\text{RAS}}$ only refresh or CBR burst refresh mode in normal read/write cycle, 1024 cycles of distributed CBR refresh with $15.6 \mu\text{s}$ interval should be executed within 16 ms immediately after exiting from and before entering into the self refresh mode.
3. If you use distributed CBR refresh mode with $15.6 \mu\text{s}$ interval in normal read/write cycle, CBR refresh should be executed within $15.6 \mu\text{s}$ immediately after exiting from and before entering into self refresh mode.
4. Repetitive self refresh mode without refreshing all memory is not allowed. Once you exit from self-refresh mode, all memory cells need to be refreshed before re-entering the self refresh mode again.

Package Dimensions

HM51(S)4170CJ/CLJ Series (CP-40DA)

Unit: mm



HM514170C, HM51S4170C Series

HM51(S)4170CTT/CLTT Series (TTP-44/40DB)

Unit: mm

