

KOI-6005B

Features


- Compliant to IrDA 1.4 Low Power Standard
- Wide Voltage Operation : 2.7 ~ 5.5V
- Compact Package Integrated Transmitter and Receiver (7.6L x 2.55W x 2.3T)
- Complete Power Down Mode for the Current Consumption.
- LED Stuck-high Protection

Applications


- Cellular Phone
- Personal Computer(Desk-top PC, Lap-top PC)
- Printers, Vending Machine, ATM
- Personal Digital Assistants.(PDA)

Dimensions

(Unit : mm)



Block Diagram



RLED $20\ \Omega \pm 0.5\%$, 0.5 Watt, $V_{cc}=2.7V$
 RLED $30\ \Omega \pm 0.5\%$, 0.5 Watt, $V_{cc}=3.3V$
 RLED $60\ \Omega \pm 0.5\%$, 0.5 Watt, $V_{cc}=5V$
 CX1 $0.47\ \mu F \pm 20\%$, Ceramic : CX2 $4.7\ \mu F \pm 20\%$, Tantalum
 CX1, CX2 must be placed 7mm of the KOI-6005B

KOI-6005B

Absolute Maximum Ratings

[Ta = 25 °C]

Parameter	Symbol	Conditions	Min.	Max.	Unit
Supply Voltage	V _{CC}	-	0	6.5	V
LED Supply Voltage	V _{LED}	-	0	6.0	V
Operating Temperature	Topr.	-	-20	85	°C
Storage Temperature	Tstg.	-	-40	100	°C
DC LED Transmit Current	I _{LED} (DC)	-	-	50	mA
Peak LED Transmit Current	I _{LED} (PK)	<90 μs pulse width, <20% duty cycle	-	200	mA
Receiver Data Output Voltage	V _{RxD}	-	-0.5	V _{CC} +0.5	V
Transmitter Data Input Voltage	V _{TxD}	-	-0.5	V _{CC} +0.5	V
Data Rate	BR	-	9.6	115.2	Kbps

4. Electro-Optical Characteristics

[Ta=25°C , V_{CC}=3.3V]

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit	
Supply Current	I _{CC1}	Shutdown	-	-	1	μA	
	I _{CC2}	Idle	-	100	200	μA	
Transmitter	Transmitter Wakeup Time	T _{tw}	-	30	200	μs	
	Viewing Angle	2Θ _{1/2}	-	30	60	deg.	
	Data Output Pulse Width	T _{stp} w	tpw(RxD)=1.63μs at 115.2kb/s	1.6	1.7	1.9	μs
	Rise Time	t _r	BR=115.2kbps	-	-	600	ns
	Fall Time	t _f		-	-	600	ns
	Peak Emission Wavelength	λ _p	-	-	875	-	nm
	Spectral Bandwidth	Δλ	-	-	45	-	nm
Receiver	Viewing Angle	2Θ _{1/2}	-	30	-	deg.	
	Peak Sensitivity Wavelength	λ _p	-	880	-	nm	
	High Level Output Voltage	V _{OH}	I _{OH} =-20 μA	V _{CC} -0.2	-	-	V
	Low Level Output Voltage	V _{OL}	I _{OL} =1mA	-	-	0.4	V
	Rx SIR Pulse Width	T _{sr} pw	tpw(RxD)=1.63μs at 115.2kb/s	1	-	4	μs
	Rise Time	t _r	BR=115.2kbps	-	-	600	ns
	Fall Time	t _f		-	-	600	ns
	Communication Distance	D		20	-	-	cm
	Receiver Latency Time	TL		-	-	100	μs
	Receiver Wakeup Time	T _{rw}		-	150	-	μs