

MM74HC151 8-Channel Digital Multiplexer

General Description

The MM74HC151 high speed Digital multiplexer utilizes advanced silicon-gate CMOS technology. Along with the high noise immunity and low power dissipation of standard CMOS integrated circuits, it possesses the ability to drive 10 LS-TTL loads. The MM74HC151 selects one of the 8 data sources, depending on the address presented on the A, B, and C inputs. It features both true (Y) and complement (W) outputs. The STROBE input must be at a low logic level to enable this multiplexer. A high logic level at the STROBE forces the W output HIGH and the Y output LOW.

The 74HC logic family is functionally as well as pin-out compatible with the standard 74LS logic family. All inputs are protected from damage due to static discharge by internal diode clamps to V_{CC} and ground.

Features


- Typical propagation delay data select to output Y: 26 ns
- Wide operating supply voltage range: 2–6V
- Low input current: 1 μ A maximum
- Low quiescent supply current: 80 μ A maximum (74HC)
- High output drive current: 4 mA minimum

Ordering Code:

| Order Number | Package Number | Package Description |
|--------------|----------------|--|
| MM74HC151M | M16A | 16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow |
| MM74HC151SJ | M16D | 16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide |
| MM74HC151MTC | MTC16 | 16-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide |
| MM74HC151N | N16E | 16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide |

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

Connection Diagram




Truth Table

| Inputs | | | Outputs | | |
|--------|---|---|-------------|----|-----------------|
| Select | | | Strobe S | Y | W |
| C | B | A | | | |
| X | X | X | H | L | H |
| L | L | L | L | D0 | $\overline{D0}$ |
| L | L | H | L | D1 | $\overline{D1}$ |
| L | H | L | L | D2 | $\overline{D2}$ |
| L | H | H | L | D3 | $\overline{D3}$ |
| H | L | L | L | D4 | $\overline{D4}$ |
| H | L | H | L | D5 | $\overline{D5}$ |
| H | H | L | L | D6 | $\overline{D6}$ |
| H | H | H | L | D7 | $\overline{D7}$ |

H = HIGH Level, L = LOW Level, X = Don't Care
D0, D1...D7 = the level of the respective D input

MM74HC151

Logic Diagram



Absolute Maximum Ratings (Note 1)

(Note 2)

| | |
|--|-------------------------|
| Supply Voltage (V_{CC}) | -0.5 to +7.0V |
| DC Input Voltage (V_{IN}) | -1.5 to $V_{CC} + 1.5V$ |
| DC Output Voltage (V_{OUT}) | -0.5 to $V_{CC} + 0.5V$ |
| Clamp Diode Current (I_{IK}, I_{OK}) | ± 20 mA |
| DC Output Current, per pin (I_{OUT}) | ± 25 mA |
| DC V_{CC} or GND Current, per pin (I_{CC}) | ± 50 mA |
| Storage Temperature Range (T_{STG}) | -65°C to +150°C |
| Power Dissipation (P_D) | |
| (Note 3) | 600 mW |
| S.O. Package only | 500 mW |
| Lead Temperature (T_L) | 260°C |
| (Soldering 10 seconds) | |

Recommended Operating Conditions

| | Min | Max | Units |
|--|-----|----------|-------|
| Supply Voltage (V_{CC}) | 2 | 6 | V |
| DC Input or Output Voltage (V_{IN}, V_{OUT}) | 0 | V_{CC} | V |
| Operating Temperature Range (T_A) | -40 | +85 | °C |
| Input Rise or Fall Times (t_r, t_f) | | | |
| $V_{CC} = 2.0V$ | | 1000 | ns |
| $V_{CC} = 4.5V$ | | 500 | ns |
| $V_{CC} = 6.0V$ | | 400 | ns |

Note 1: Absolute Maximum Ratings are those values beyond which damage to the device may occur.

Note 2: Unless otherwise specified all voltages are referenced to ground.

Note 3: Power Dissipation temperature derating — plastic "N" package: — 12 mW/°C from 65°C to 85°C.



DC Electrical Characteristics (Note 4)

| Symbol | Parameter | Conditions | V_{CC} | $T_A = 25^\circ C$ | | | $T_A = -40 \text{ to } 85^\circ C$ | | | $T_A = -55 \text{ to } 125^\circ C$ | | | Units |
|----------|-----------------------------------|--|----------|--------------------|-------------------|-----------|------------------------------------|--|-------------------|-------------------------------------|---------|---|-------|
| | | | | Typ | Guaranteed Limits | | Guaranteed Limits | | Guaranteed Limits | | | | |
| V_{IH} | Minimum HIGH Level Input Voltage | | 2.0V | | 1.5 | 1.5 | 1.5 | | | | | V | |
| | | | 4.5V | | 3.15 | 3.15 | 3.15 | | | | V | | |
| | | | 6.0V | | 4.2 | 4.2 | 4.2 | | | | V | | |
| V_{IL} | Maximum LOW Level Input Voltage | | 2.0V | | 0.5 | 0.5 | 0.5 | | | | | V | |
| | | | 4.5V | | 1.35 | 1.35 | 1.35 | | | | V | | |
| | | | 6.0V | | 1.8 | 1.8 | 1.8 | | | | V | | |
| V_{OH} | Minimum HIGH Level Output Voltage | $V_{IN} = V_{IH} \text{ or } V_{IL}$ $ I_{OUT} \leq 20 \mu A$ | 2.0V | 2.0 | 1.9 | 1.9 | 1.9 | | | | | V | |
| | | | 4.5V | 4.5 | 4.4 | 4.4 | 4.4 | | | | V | | |
| | | | 6.0V | 6.0 | 5.9 | 5.9 | 5.9 | | | | V | | |
| | | $V_{IN} = V_{IH} \text{ or } V_{IL}$ $ I_{OUT} \leq 4.0 \text{ mA}$ $ I_{OUT} \leq 5.2 \text{ mA}$ | 4.5V | 4.2 | 3.98 | 3.84 | 3.7 | | | | V | | |
| | | | 6.0V | 5.7 | 5.48 | 5.34 | 5.2 | | | | V | | |
| | | | | | | | | | | | | | |
| V_{OL} | Maximum LOW Level Output Voltage | $V_{IN} = V_{IH} \text{ or } V_{IL}$ $ I_{OUT} \leq 20 \mu A$ | 2.0V | 0 | 0.1 | 0.1 | 0.1 | | | | | V | |
| | | | 4.5V | 0 | 0.1 | 0.1 | 0.1 | | | | V | | |
| | | | 6.0V | 0 | 0.1 | 0.1 | 0.1 | | | | V | | |
| | | $V_{IN} = V_{IH} \text{ or } V_{IL}$ $ I_{OUT} \leq 4.0 \text{ mA}$ $ I_{OUT} \leq 5.2 \text{ mA}$ | 4.5V | 0.2 | 0.26 | 0.33 | 0.4 | | | | V | | |
| | | | 6.0V | 0.2 | 0.26 | 0.33 | 0.4 | | | | V | | |
| | | | | | | | | | | | | | |
| I_{IN} | Maximum Input Current | $V_{IN} = V_{CC} \text{ or } GND$ | 6.0V | | ± 0.1 | ± 1.0 | ± 1.0 | | | | μA | | |
| I_{CC} | Maximum Quiescent Supply Current | $V_{IN} = V_{CC} \text{ or } GND$ $I_{OUT} = 0 \mu A$ | 6.0V | | 8.0 | 80 | 160 | | | | μA | | |




Note 4: For a power supply of $5V \pm 10\%$ the worst case output voltages (V_{OH} and V_{OL}) occur for HC at 4.5V. Thus the 4.5V values should be used when designing with this supply. Worst case V_{IH} and V_{IL} occur at $V_{CC} = 5.5V$ and 4.5V respectively. (The V_{IH} value at 5.5V is 3.85V.) The worst case leakage current (I_{IN} , I_{CC} , and I_{OZ}) occur for CMOS at the higher voltage and so the 6.0V values should be used.

| AC Electrical Characteristics | | | | | | | | |
|---|---|---------------|----------|--------------------|-------------------|------------------------------------|-------------------------------------|-------|
| $V_{CC} = 5V, T_A = 25^\circ C, C_L = 15 \text{ pF}, t_r = t_f = 6 \text{ ns}$ | | | | | | | | |
| Symbol | Parameter | Conditions | Typ | Guaranteed Limit | Units | | | |
| t_{PHL}, t_{PLH} | Maximum Propagation Delay A, B or C to Y | | 26 | 35 | ns | | | |
| t_{PHL}, t_{PLH} | Maximum Propagation Delay A, B or C to W | | 27 | 35 | ns | | | |
| t_{PHL}, t_{PLH} | Maximum Propagation Delay Any D to Y | | 22 | 29 | ns | | | |
| t_{PHL}, t_{PLH} | Maximum Propagation Delay any D to W | | 24 | 32 | ns | | | |
| t_{PHL}, t_{PLH} | Maximum Propagation Delay Strobe to Y | | 17 | 23 | ns | | | |
| t_{PHL}, t_{PLH} | Maximum Propagation Delay Strobe to W | | 16 | 21 | ns | | | |
| AC Electrical Characteristics | | | | | | | | |
| $C_L = 50 \text{ pF}, t_r = t_f = 6 \text{ ns}$ (unless otherwise specified) | | | | | | | | |
| Symbol | Parameter | Conditions | V_{CC} | $T_A = 25^\circ C$ | | $T_A = -40 \text{ to } 85^\circ C$ | $T_A = -55 \text{ to } 125^\circ C$ | Units |
| | | | | Typ | Guaranteed Limits | | | |
| t_{PHL}, t_{PLH} | Maximum Propagation Delay A, B or C to Y | | 2.0V | 90 | 205 | 256 | 300 | ns |
| | | | 4.5V | 31 | 41 | 51 | 60 | ns |
| | | | 6.0V | 26 | 35 | 44 | 51 | ns |
| t_{PHL}, t_{PLH} | Maximum Propagation Delay A, B or C to W | | 2.0V | 95 | 205 | 256 | 300 | ns |
| | | | 4.5V | 32 | 41 | 51 | 60 | ns |
| | | | 6.0V | 27 | 35 | 44 | 51 | ns |
| t_{PHL}, t_{PLH} | Maximum Propagation Delay any D to Y | | 2.0V | 70 | 195 | 244 | 283 | ns |
| | | | 4.5V | 27 | 39 | 49 | 57 | ns |
| | | | 6.0V | 23 | 33 | 41 | 48 | ns |
| t_{PHL}, t_{PLH} | Maximum Propagation Delay any D to W | | 2.0V | 75 | 185 | 231 | 268 | ns |
| | | | 4.5V | 29 | 37 | 46 | 54 | ns |
| | | | 6.0V | 25 | 32 | 40 | 46 | ns |
| t_{PHL}, t_{PLH} | Maximum Propagation Delay Strobe to Y | | 2.0V | 50 | 140 | 175 | 203 | ns |
| | | | 4.5V | 21 | 28 | 35 | 41 | ns |
| | | | 6.0V | 18 | 24 | 30 | 35 | ns |
| t_{PHL}, t_{PLH} | Maximum Propagation Delay Strobe to W | | 2.0V | 45 | 127 | 159 | 185 | ns |
| | | | 4.5V | 20 | 25 | 32 | 37 | ns |
| | | | 6.0V | 17 | 22 | 28 | 32 | ns |
| t_{TLH}, t_{THL} | Maximum Output Rise and Fall Time | | 2.0V | 30 | 75 | 95 | 110 | ns |
| | | | 4.5V | 8 | 15 | 19 | 22 | ns |
| | | | 6.0V | 7 | 13 | 16 | 19 | ns |
| C_{PD} | Power Dissipation Capacitance (Note 5) | (per package) | | 110 | | | | pF |
| C_{IN} | Maximum Input Capacitance | | | 5 | 10 | 10 | 10 | pF |
| <p>Note 5: C_{PD} determines the no load dynamic power consumption, $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$, and the no load dynamic current consumption, $I_S = C_{PD} V_{CC} f + I_{CC}$.</p> | | | | | | | | |

Physical Dimensions inches (millimeters) unless otherwise noted




16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow Package Number M16A



16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide Package Number M16D

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



**16-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide
Package Number MTC16**

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide Package Number N16E

N16E (REV F)

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com