



MMVL3401

SURFACE MOUNT PIN DIODE

VOLTAGE 35 Volts **POWER** 200 mW


SOD-323 Unit: inch (mm)

FEATURES

- Very low series resistance at 100MHz (0.45 Ω typical@ $I_F=10mA$)
- Low capacitance (0.8pF typical@ $V_R=20V$)
- Surface mount package ideally suited for automatic insertion
- Pb free product are available : 99% Sn above can meet RoHS environment substance directive request

MECHANICAL DATA

- Case: SOD-323 plastic
- Terminals : Solderable per MIL-STD-750,Method 2026
- Approx Weight: 0.008 grams
- Device Marking : V34



ABSOLUTE RATINGS

PARAMETER	SYMBOL	VALUE	UNITS
Maximum Reverse Voltage	V_R	35	V
Continuous Forward Current	I_F	0.2	A
Power Dissipation ⁽¹⁾	P_{TOT}	200	mW
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	$^{\circ}C$

THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	VALUE	UNITS
Thermal Resistance , Junction to Ambient ⁽¹⁾	$R_{\theta JA}$	625	$^{\circ}C/W$

Note 1 : FR-5 Board 1.0 x 0.75 x 0.062 in.







MMVL3401

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$, unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Breakdown Voltage	$V_{(BR)}$	$I_R=10\mu\text{A}$	35	-	-	V
Reverse Current	I_R	$V_R=25\text{V}$	-	-	100	nA
Series Resistance	R_S	$I_F=10\text{mA}, f=100\text{MHz}$	-	0.45	0.7	Ω
Total Capacitance	C_T	$f=1.0\text{MHz}; V_R=20\text{V}$	-	-	1.0	pF


ELECTRICAL CHARACTERISTICS CURVE





MMVL3401

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
 - T/R - 12K per 13" plastic Reel
 - T/R - 5K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2005

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.