

MPV5 Series


9x14 mm, 5.0 Volt, PECL, VCXO






- LVDS and PECL Output Logic With Good Integrated Jitter Performance (5 ps)
- Phase-Locked Loops (PLL's), Clock Recovery, Reference Signal Tracking, Synthesizers, Frequency Modulation/ Demodulation

Ordering Information

Product Series	MPV5	1	0	R	1	P	J	00.0000 MHz
Temperature Range								
1: 0°C to +70°C								
2: -40°C to +85°C								
6: -20°C to +70°C								
8: 0°C to +50°C								
Stability								
0: Nominal per APR selection								
Output Type								
R: Complementary, Tri-state								
Z: Complementary, Non Tri-state								
T: Single, Tri-state								
X: Single, Non Tri-state								
Absolute Pull Range								
1: ±50 ppm (±35 ppm typ. Stability)								
2: ±100 ppm (±20 ppm typ. Stability)								
5: ±80 ppm (±25 ppm typ. Stability)								
8: ±25 ppm (±50 ppm typ. Stability)								
Symmetry/Output Logic Type								
P: 45/55% PECL								
Q: 40/60% PECL								
Package/Lead Configurations								
J: J-lead								
Frequency (customer specified)								



OBSOLETE




All dimensions
in inches (mm).

Pin Connections

PIN	FUNCTION
1	Control Voltage
2	Tri-state or N/C
3	Ground/Case
4	Output Q
5	Output $\overline{Q}$ or N/C
6	+Vcc

SUGGESTED SOLDER PAD LAYOUT



M-tron reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of such product.

M-tron Industries, Inc., PO Box 630, Yankton, SD 57078-0630, USA Phone: 605-665-9321 or 1-800-762-8800 Fax: 605-665-1709 Website: www.mtron.com
M-tron Industries Limited, 1104 Shanghai Industrial Investment Building, 48-62 Hennessy Road, Wanchai, Hong Kong, China Phone: 852-2866-8023 Fax: 852-2529-1822

MPV5 Series

9x14 mm, 5.0 Volt, PECL, VCXO



	Electrical Specifications						
	PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition
	Frequency Range	F	0.75		800	MHz	See Note 1
	Frequency Stability	$\Delta F/F$	(See Ordering Information)				See Note 2
	Operating Temperature	Ts	-40		+85	°C	See ordering info.
	Storage Temperature	Ta	-55		+125	°C	
	Input Voltage	Vcc	4.75	5.0	5.25	V	
	Input Current	Idd					
	0.75 MHz to 24 MHz				60	mA	
	24 MHz to 160 MHz				100	mA	
	160 MHz to 800 MHz				120	mA	
	Symmetry (Duty Cycle)		40	50	60	%	@ Vcc -1.3 VDC
	Load						See Note 3
	Rise/Fall Time	Tr/Tf		.35	.55	ns	@ 20/80%
	Logic Level	Vcc					
	Logic Level	Vcc					
	Cycle time						
	@ 38.88 MHz			5		ps RMS	Sigma
	@ 155.52 MHz						
	@ 622.08 MHz			10	20	ps RMS	
	Phase Jitter	ϕJ					Integrated 12 kHz - 20 MHz
	@ 38.88 MHz			.3	.5	ps RMS	
	@ 155.52 MHz			3	5	ps RMS	
	@ 622.08 MHz			3	5	ps RMS	
	Peak to Peak Jitter (+/-)	Tj					@ BER 1E-12
	@ 38.88 MHz			2.1	3.5	ps RMS	
	@ 155.52 MHz			21	35	ps RMS	
	@ 622.08 MHz			21	35	ps RMS	
	Phase Noise (Typical)						Offset from carrier
	@ 38.88 MHz	10 Hz	100 Hz	1 kHz	10 kHz	100 kHz	dBc/Hz
	@ 155.52 MHz	-65	-97	-127	-143	-153	dBc/Hz
	@ 622.08 MHz	-50	-80	-112	-128	-125	dBc/Hz
		-50	-80	-110	-123	-120	dBc/Hz
	Modulation Bandwidth	fm			10k	Hz	-3 dB bandwidth
	Input Impedance	Zin	50			K Ω	
	Control Voltage	Vcc	0.5	2.5	5	V	Pin 1 voltage
	Center Frequency	Vc0		2.5		V	
	Linearity			5	10	%	
	Pullability	APR	(See Ordering Information)				See Note 4
	Tri-state Output "On"	OE	2.8			V	Pin 2 voltage
	Tri-state Output "Off"	OE			0.6	V	Pin 2 voltage
Environmental	Mechanical Shock	Per MIL-STD-202, Method 213, Condition C					
	Vibration	Per MIL-STD-202, Method 201 & 204					
	Reflow Solder Conditions	See "Figure 2" on page 147					
	Hermeticity	Per MIL-STD-202, Method 112 (1 x 10 ⁻⁵ atm.cc/s of helium)					
	Solderability	Per MIL-STD-883, Method 2003					

1. Frequencies above 70 MHz utilize a PLL design. Fundamental and PLL designs are available for other frequencies. Contact factory.
2. Stability is given for deviation over temperature.
3. PECL load - see load circuit diagram #3 on page 148.
4. APR specification inclusive of initial tolerance, deviation over temperature, shock, vibration, supply voltage, and aging.

M-tron reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of such product.

M-tron Industries, Inc., PO Box 630, Yankton, SD 57078-0630, USA Phone: 605-665-9321 or 1-800-762-8800 Fax: 605-665-1709 Website: www.mtron.com
M-tron Industries Limited, 1104 Shanghai Industrial Investment Building, 48-62 Hennessy Road, Wanchai, Hong Kong, China Phone: 852-2866-8023 Fax: 852-2529-1822