


## Single Supply Single Operational Amplifier with Full Swing Output

### ■ GENERAL DESCRIPTION

The NJM2741 is a low supply voltage operational amplifier with Full swing output.

It is suitable for audio section of portable sets, PCs and any General-purpose use.

### ■ PACKAGE OUTLINE



**NJM2741F**




**NJM2741F3**

### ■ FEATURES

- Operating Voltage : 2.5V to 14V
- Output Full Swing :  $V_{OH} \geq 4.9V$  Typ. (at  $V^+ = 5V, R_L = 5k\Omega$ )  
:  $V_{OL} \leq 0.1V$  Typ. (at  $V^+ = 5V, R_L = 5k\Omega$ )
- Offset Voltage : 1mV Typ
- Slew Rate : 3.5V/ $\mu s$  Typ.
- Low Distortion : 0.001% typ. (at  $V^+ = 5V, f = 1kHz$ )
- Low Input Voltage Noise : 10nV/ $\sqrt{Hz}$  typ.
- Bipolar Technology
- Package Outline : MTP5, SC88A

### ■ PIN CONFIGURATION



**NJM2741F**  
**NJM2741F3**  
(Top View)

### PIN FUNCTION

1. +INPUT
2. GND
3. -INPUT
4. OUTPUT
5.  $V^+$

## ■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	$V^+$	15	V
Differential Input Voltage Range	$V_{ID}$	$\pm 15$ (Note1)	V
Common Mode Input Voltage Range	$V_{ICM}$	0 to 15 (Note1)	V
Power Dissipation	$P_D$	390[MTP5] (Note2) 280[SC88A] (Note2)	mW
Operating Temperature Range	$T_{opr}$	-40 to +85	$^{\circ}C$
Storage Temperature Range	$T_{stg}$	-50 to +125	$^{\circ}C$

(Note1) For supply voltage less than 15V, the absolute maximum input voltage is equal to the supply voltage.

(Note2) On the PCB "EIA/JEDEC (76.2x114.3x1.6mm, two layers, FR-4)"

## ■ OPERATING VOLTAGE ( $T_a=25^{\circ}C$ )

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	$V^+$	2.5 to 14	V

## ■ ELECTRICAL CHARACTERISTICS

### ●DC CHARACTERISTICS ( $V^+=5V, T_a=25^{\circ}C$ )

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Operating Current	$I_{CC}$	$R_L=\infty, V_{IN}=2.5V,$ No Signal Apply	-	2.2	3.3	mA
Input Offset Voltage	$V_{IO}$	$R_S \leq 10k\Omega$	-	1	6	mV
Input Bias Current	$I_B$		-	100	350	nA
Input Offset Current	$I_{IO}$		-	5	100	nA
Large Signal Voltage Gain	$A_V$	$R_L \geq 10k\Omega$ to 2.5V, $V_o=0.5V$ to 4.5V	65	85	-	dB
Common Mode Rejection Ratio	CMR	$0V \leq V_{CM} \leq 4V$	60	75	-	dB
Supply Voltage Rejection Ratio	SVR	$V^+=2.5V$ to 14V, $V_{CM}=V^+/2$	60	80	-	dB
Output Voltage	$V_{OH}$	$R_L=5k\Omega$ to 2.5V	4.75	4.9	-	V
	$V_{OL}$	$R_L=5k\Omega$ to 2.5V	-	0.1	0.25	V
Input Common Mode Voltage Range	$V_{ICM}$	CMR $\geq 60dB$	0	-	4	V

### ●AC CHARACTERISTICS ( $V^+=5V, T_a=25^{\circ}C$ )

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Unity Gain Bandwidth	GB	$f=10kHz, R_L=10k\Omega$ to 2.5V	-	10	-	MHz
Phase Margin	$\Phi_M$	$R_L=10k\Omega$ to 2.5V, $C_L=10pF$	-	75	-	Deg
Equivalent Input Noise Voltage	$V_{NI}$	$f=1kHz, V_{CM}=2.5V$	-	10	-	nV/ $\sqrt{Hz}$
Total Harmonic Distortion	THD	$f=1kHz, A_V=+2$ $R_L=10k\Omega$ to 2.5V, $V_o=1.5V_{rms}$	-	0.001	-	%

### ●AC CHARACTERISTICS ( $V^+=5V, T_a=25^{\circ}C$ )

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Slew Rate	SR	(Note 3), $A_V=1, V_{IN}=2V_{pp}$ $R_L=10k\Omega$ to 2.5V, $C_L=10pF$	-	3.5	-	V/ $\mu s$

(Note 3) Number specified is the slower of the positive and negative slew rates.

#### [CAUTION]

The specifications on this data book are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this data book are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.