

## APPLICATIONS

- ✓ Cellular Phones
- ✓ MCM Boards
- ✓ Wireless Communication Circuits
- ✓ IR LEDs
- ✓ SMART & PCMCIA Cards

## IEC COMPATIBILITY (EN61000-4)

- ✓ 61000-4-2 (ESD): Air - 15kV, Contact - 8kV
- ✓ 61000-4-4 (EFT): 40A - 5/50ns

## FEATURES


- ✓ ESD Protection > 25 kilovolts
- ✓ Available in Multiple Voltage Types Ranging From 3.3V to 36V
- ✓ 250 Watts Peak Pulse Power per Line ( $t_p = 8/20\mu s$ )
- ✓ Bidirectional Configuration & Monolithic Structure
- ✓ Protects 1 to 3 Lines
- ✓ RoHS Compliant in Lead-Free Versions

## MECHANICAL CHARACTERISTICS

- ✓ Standard EIA Chip Size: 0404
- ✓ Weight 0.73 milligrams (Approximate)
- ✓ Available in Tin-Lead or Lead-Free Plating
- ✓ Solder Reflow Temperature:
  - Tin-Lead - Sn/Pb, 85/15: 240-245°C
  - Lead-Free - Sn/Ag/Cu, 96/3.5/0.5: 260-270°C
- ✓ Flammability Rating UL 94V-0
- ✓ 8mm Plastic & Paper Tape and Reel Per EIA Standard 481
- ✓ Device Marking On Reel
- ✓ Top Contacts: Solder Bump 0.004" in Height (Nominal)



## PIN CONFIGURATION





**DEVICE CHARACTERISTICS**

MAXIMUM RATINGS @ 25°C Unless Otherwise Specified			
PARAMETER	SYMBOL	VALUE	UNITS
Peak Pulse Power ( $t_p = 8/20\mu s$ ) - See Figure 1	$P_{PP}$	250	Watts
Operating Temperature	$T_J$	-55°C to 150°C	°C
Storage Temperature	$T_{STG}$	-55°C to 150°C	°C




ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified						
PART NUMBER (See Note 1)	RATED STAND-OFF VOLTAGE  $V_{WM}$ VOLTS	MINIMUM BREAKDOWN VOLTAGE  @ 1mA $V_{(BR)}$ VOLTS	MAXIMUM CLAMPING VOLTAGE (See Fig. 2)  @ $I_p = 1A$ $V_C$ VOLTS	MAXIMUM CLAMPING VOLTAGE (See Fig. 2)  @ 8/20 $\mu s$ $V_C @ I_{PP}$	MAXIMUM LEAKAGE CURRENT (See Note 2)  @ $V_{WM}$ $I_D$ $\mu A$	TYPICAL CAPACITANCE  @ 0V, 1 MHz C pF
P0404FC05C	5.0	6.0	9.8	14.7V @ 17A	10**	100
P0404FC08C	8.0	8.5	13.4	19.2V @ 13A	10***	75
P0404FC12C	12.0	13.3	19.0	29.7V @ 9.0A	1	50
P0404FC15C	15.0	16.7	24.0	35.7V @ 7.0A	1	40
P0404FC24C	24.0	26.7	43.0	55.0V @ 5.0A	1	30
P0404FC36C	36.0	40.0	64.0	84.0V @ 3.0A	1	25

**Note 1:** All devices are bidirectional. Electrical characteristics apply in both directions.

**Note 2:** \*Maximum leakage current < 5 $\mu A$  @ 2.8V. \*\*Maximum leakage current < 500nA @ 3.3V. \*\*\*Maximum leakage current < 200nA @ 5V.



GRAPHS





**APPLICATION INFORMATION**

PRINTED CIRCUIT BOARD RECOMMENDATIONS	
PARAMETER	VALUE
Pad Size on PCB	0.275mm
Pad Shape	Round
Pad Definition	Non-Solder Mask Defined Pads
Solder Mask Opening	0.325mm Round
Solder Stencil Thickness	0.150mm
Solder Stencil Aperture Opening (laser cut, 5% tapered walls)	0.330mm Round
Solder Paste Type	No Clean
Pad Protective Finish	OSP(Entek Cu Plus 106A)
Tolerance - Edge To Corner Ball	±50µm
Solder Ball Side Coplanarity	±20µm
Maximum Dwell Time Above Liquidous (183°C)	60 Seconds
Soldering Maximum Temperature	270°C



REQUIREMENTS
<p><b>Temperature:</b>  <math>T_p</math> for Lead-Free (SnAgCu): 260-265°C  <math>T_p</math> for Tin-Lead: 240-245°C                      Preheat time and temperature depends on solder paste and flux activation temperature, component size, weight, surface area &amp; plating.</p>

**RECOMMENDED NON-SOLDER MASK DEFINED PAD ILLUSTRATION**




# P0404FC3.3C\* thru P0404FC24C\*

## PACKAGE OUTLINE & DIMENSIONS

PACKAGE OUTLINE		PACKAGE DIMENSIONS			
		<b>DIM</b>	<b>MILLIMETERS</b>	<b>INCHES</b>	
A	0.56 NOM	0.022 NOM			
B	0.86 NOM	0.034 NOM			
C	1.0 ± 0.02	0.039 ± 0.001			
E	0.15 SQ	0.006 SQ			
F	1.0 ± 0.0254	0.039 ± 0.001			
G	0.15 NOM	0.006 NOM			
H	0.127 MAX 0.076 MIN	0.005 MAX 0.003 MIN			
I	0.406 NOM	0.016 NOM			
<p><b>NOTES:</b></p> <ol style="list-style-type: none"> <li>Controlling dimensions in inches.</li> <li>Decimal tolerances for mounting pad and outline: .xxx ± 0.05mm (± 0.002").</li> </ol>					
MOUNTING PAD LAYOUT - Option 1		PAD DIMENSIONS			
		<b>DIM</b>	<b>MILLIMETERS</b>	<b>INCHES</b>	
A	0.51	0.020			
C	0.30	0.012			
D	0.46	0.018			
E	0.20	0.008			
F	0.15 SQ	0.006 SQ			
G	0.71	0.028			
H	0.99	0.039			
I	0.51	0.020			
<p><b>NOTE:</b></p> <ol style="list-style-type: none"> <li><i>Preferred:</i> Using 0.1mm (0.004") stencil.</li> </ol>					
<p><b>Outline &amp; Dimensions: Rev 4 - 9/04, 06022</b></p>					

**PACKAGE OUTLINE & DIMENSIONS**

MOUNTING PAD LAYOUT - Option 2



**PACKAGE DIMENSIONS**


DIM	MILLIMETERS	INCHES
A	0.51	0.020
F	0.15 SQ	0.006 SQ
G	0.71	0.028
H	0.99	0.039
I	0.51	0.020

**NOTES:**

1. Controlling dimensions in inches.
2. Decimal tolerances for mounting pad and outline: .xxx ± 0.05mm (± 0.002").
3. Preferred: Using 0.1mm (0.004") stencil.

**Outline & Dimensions: Rev 4 - 9/04, 06022**

**TAPE & REEL ORIENTATION**



**NOTE:**

1. Top view of tape. Solder bumps are face down in tape package.

**TAPE & REEL ORDERING NOMENCLATURE**

1. Surface mount product is taped and reeled in accordance with EIA 481.
2. 8mm Plastic Tape: 7 Inch Reels - 5,000 pieces per reel. Ordering Suffix: -T75-1 (i.e., P0404FC05C-T75-1).
3. 8mm Paper Tape: 7 Inch Reels - 10,000 pieces per reel. Ordering Suffix: -T710-2 (i.e., P0404FC05C-T710-2).
4. Suffix = LF = Lead-Free, i.e., P0404FC05C-LF-T75-1.

**COPYRIGHT © ProTek Devices 2005**

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.

**ProTek Devices**  
 2929 South Fair Lane, Tempe, AZ 85282  
 Tel: 602-431-8101 Fax: 602-431-2288  
 E-Mail: [sales@protekdevices.com](mailto:sales@protekdevices.com)  
 Web Site: [www.protekdevices.com](http://www.protekdevices.com)