

# PIC18 Microcontroller Family

The PIC18 microcontroller family provides PICmicro® devices in 18- to 80-pin packages, that are both socket and software upwardly compatible to the PIC16 family. The PIC18 family includes all the popular peripherals, such as MSSP, ESCI, CCP, flexible 8- and 16-bit timers, PSP, 10-bit ADC, WDT, POR and CAN 2.0B Active for the maximum flexible solution. Most PIC18 devices will provide FLASH program memory in sizes from 8 to 128 Kbytes and data RAM from 256 to 4 Kbytes; operating from 2.0 to 5.5 volts, at speeds from DC to 40 MHz. Optimized for high-level languages like ANSI C, the PIC18 family offers a highly flexible solution for complex embedded applications.

## High Performance RISC CPU:

- 77 instructions
- C-Language friendly architecture
- PIC16 source code compatible
- Linear program memory addressing to 2 Mbyte
- Linear data memory addressing up to 4 Kbytes
- Up to 10 MIPs operation:
  - DC - 40 MHz osc/clock input
  - 4 MHz - 10 MHz clock with PLL active
- 16-bit wide instructions, 8-bit wide data path
- Priority levels for interrupts
- 8 x 8 Single Cycle Hardware Multiplier

## Peripheral Features:

- High current sink/source 25 mA/25 mA
- Up to four external interrupt pins
- Up to three 16-bit timer/counters
- Up to two 8-bit timer/counters with 8-bit period register (time-base for PWM)
- Secondary LP oscillator clock option - Timer1
- Up to five Capture/Compare/PWM (CCP) modules  
CCP pins can be configured as:
  - Capture input: 16-bit, resolution 6.25 ns ( $T_{cy}/16$ )
  - Compare: 16-bit, max. resolution 100 ns ( $T_{cy}$ )
  - PWM output: PWM resolution is 1- to 10-bit  
Max. PWM frequency @: 8-bit resolution = 156 kHz  
10-bit resolution = 39 kHz
- Master Synchronous Serial Port (MSSP) module  
Two modes of operation:
  - 3-wire SPI™ (supports all 4 SPI modes)
  - I<sup>2</sup>C™ Master and Slave mode
- Up to 2 Addressable USART modules (ESCI)
  - Supports interrupt on Address bit
- Parallel Slave Port (PSP) module

## Analog Features:

- 10-bit Analog-to-Digital Converter module (A/D) with:
  - Fast sampling rate
  - Up to 16 channels input multiplexor
  - Conversion available during SLEEP
  - DNL =  $\pm 1$  LSb, INL =  $\pm 1$  LSb



## Analog Features (Continued):

- Programmable Low Voltage Detection (LVD) module
  - Supports interrupt-on-low voltage detection
- Programmable Brown-out Reset (BOR)
- Comparators

## Special Microcontroller Features:

- Power-on Reset (POR), Power-up Timer (PWRT) and Oscillator Start-up Timer (OST)
- Watchdog Timer (WDT) with its own on-chip RC oscillator for reliable operation
- Programmable code protection
- In-Circuit Serial Programming™ (ICSP™) via two pins

## CMOS Technology:

- Fully static design
- Wide operating voltage range (2.0V to 5.5V)
- Industrial and Extended temperature ranges

## Power Managed Features:

- Dynamically switch to secondary LP oscillator
- Internal RC oscillator for ADC operation during SLEEP
- SLEEP mode ( $I_{PD} < 1 \mu A$  typ.)
  - up to 23 individually selectable wake-up events
  - 3 edge selectable wake-up inputs
  - 4 state change wake-up inputs
- Internal RC oscillator for WDT (period wake-up)
- RAM retention mode ( $V_{DD}$  as low as 1.5V)
- Up to 6 more Power Managed modes available on selected models (PIC18F1320/2320/4320 and PIC18F1220/2220/4220)



**MICROCHIP**  
PICmicro® Microcontrollers

## Additional Information:

- Microchip's web site: [www.microchip.com](http://www.microchip.com)
- Microchip's PICmicro 18C MCU Reference Manual, Order No. DS39500
- Microchip's CD-ROMs available:
  - Technical Library, Order No. DS00161
- Microchip's Data Sheets available:
  - PIC18CXX2, Order No. DS39026
  - PIC18CXX8, Order No. DS30475
  - PIC18C601/801, Order No. DS39541
- Application Notes are available in:
  - Embedded Control Handbook, Order No. DS00092
  - Embedded Control Handbook, Volume 2, Math Library, Order No. DS00167
  - Embedded Control Handbook Update 2000, Order No. DS00711
- Microchip's Quality Systems and Customer Interface System, Order No. DS00169
- Demo Boards Available:
  - PICDEM™ 2 Demonstration Board
  - ROMless
  - CAN/LIN bus
- Third Party Tools Available:
  - C Compilers
    - HI-TECH - PICC™, [www.htsoft.com](http://www.htsoft.com)
    - IAR - EWB-PIC, [www.iar.com](http://www.iar.com)
    - CCS PIC18 C Compiler, [www.ccsinfo.com](http://www.ccsinfo.com)

## PIC18 Microcontroller Family

Product	Program Memory		Data Memory		I/O Ports	ADC 10-bit	MSSP	USART	Other	CCP/PWM	Timers 8/16-bit	Packages	Pins
	Type	Bytes	RAM Bytes	EEPROM Bytes									
PIC18F1220	FLASH	4K	256	256	16	7	—	1	6x PMM	1	1/3	DIP, SOIC, SSOP, QFN	18
PIC18F1320	FLASH	8K	256	256	16	7	—	1	6x PMM	1	1/3	DIP, SOIC, SSOP, QFN	18
PIC18F2220	FLASH	4K	512	256	23	10	I <sup>2</sup> C/SPI	1	6x PMM	2	1/3	DIP, SOIC	28
PIC18F2320	FLASH	8K	512	256	23	10	I <sup>2</sup> C/SPI	1	6x PMM	2	1/3	DIP, SOIC	28
PIC18C242	OTP	16K	512	—	23	5	I <sup>2</sup> C/SPI	1	—	2	1/3	DIP, SOIC	28
PIC18C252	OTP	32K	1536	—	23	5	I <sup>2</sup> C/SPI	1	—	2	1/3	DIP, SOIC	28
PIC18F242	FLASH	16K	512	256	23	5	I <sup>2</sup> C/SPI	1	—	2	1/3	DIP, SOIC, SSOP	28
PIC18F252	FLASH	32K	1536	256	23	5	I <sup>2</sup> C/SPI	1	—	2	1/3	DIP, SOIC, SSOP	28
PIC18F258	FLASH	32K	1536	256	22	5	I <sup>2</sup> C/SPI	1	CAN 2.0B	1	1/3	DIP, SOIC	28
PIC18F4220	FLASH	4K	512	256	34	13	I <sup>2</sup> C/SPI	1	6x PMM	2	1/3	DIP, TQFP, QFN	40/44
PIC18F4320	FLASH	8K	512	256	34	13	I <sup>2</sup> C/SPI	1	6x PMM	2	1/3	DIP, TQFP, QFN	40/44
PIC18C442	OTP	16K	512	—	34	8	I <sup>2</sup> C/SPI	1	—	2	1/3	DIP, PLCC, TQFP	40/44
PIC18C452	OTP	32K	1536	—	34	8	I <sup>2</sup> C/SPI	1	—	2	1/3	DIP, PLCC, TQFP	40/44
PIC18F442	FLASH	16K	512	256	34	8	I <sup>2</sup> C/SPI	1	—	2	1/3	DIP, PLCC, TQFP	40/44
PIC18F452	FLASH	32K	1536	256	34	8	I <sup>2</sup> C/SPI	1	—	2	1/3	DIP, PLCC, TQFP	40/44
PIC18F458	FLASH	32K	1536	256	33	5	I <sup>2</sup> C/SPI	1	CAN 2.0B	1	1/3	DIP, PLCC, TQFP	40/44
PIC18C601	—	ROMless	1536	—	31	8	I <sup>2</sup> C/SPI	1	—	2	1/3	PLCC, TQFP	64/68
PIC18C658	OTP	32K	1536	—	52	12	I <sup>2</sup> C/SPI	1	CAN 2.0B	2	1/3	PLCC, TQFP	64/68
PIC18F6520	FLASH	32K	2048	1024	52	12	I <sup>2</sup> C/SPI	2	—	5	2/3	TQFP	64
PIC18F6620	FLASH	64K	3840	1024	52	12	I <sup>2</sup> C/SPI	2	—	5	2/3	TQFP	64
PIC18F6720	FLASH	128K	3840	1024	52	12	I <sup>2</sup> C/SPI	2	—	5	2/3	TQFP	64
PIC18C801	—	ROMless	1536	—	42	12	I <sup>2</sup> C/SPI	1	—	2	1/3	PLCC, TQFP	80/84
PIC18C858	OTP	32K	1536	—	68	16	I <sup>2</sup> C/SPI	1	CAN 2.0B	2	1/3	PLCC, TQFP	80/84
PIC18F8520	FLASH	32K	2048	1024	68	16	I <sup>2</sup> C/SPI	2	EMA	5	2/3	TQFP	80
PIC18F8620	FLASH	64K	3840	1024	68	16	I <sup>2</sup> C/SPI	2	EMA	5	2/3	TQFP	80
PIC18F8720	FLASH	128K	3840	1024	68	16	I <sup>2</sup> C/SPI	2	EMA	5	2/3	TQFP	80

**Abbreviation:** ADC = Analog-to-Digital Converter    CCP = Capture/Compare/PWM    I<sup>2</sup>C = Inter-Integrated Circuit Bus    PMM = Power Managed Mode  
 PWM = Pulse Width Modulation    SPI = Serial Peripheral Interface    USART = Universal Synchronous/Asynchronous Receiver/Transmitter

Development Tools from Microchip		Resale Price*
MPLAB® IDE	Integrated Development Environment (IDE)	FREE
MPASM™ Assembler	Universal PICmicro Macro-Assembler	FREE
MPLINK™ Linker/MPLIB™ Librarian	Linker/Librarian	FREE
MPLAB® SIM	Software Simulator	FREE
MPLAB® ICE 2000/4000	Full Featured Modular In-Circuit Emulator	Starting at \$2,045
MPLAB® ICD 2	In-Circuit Debugger	Starting at \$159
C compiler	Microchip MPLAB® C18 or supported by third-party vendors (HI-TECH, IAR, CCS)	Contact Vendor
PRO MATE® II Device Programmer	Full Featured Modular Device Programmer	Starting at \$854
PICSTART® Plus Programmer	Entry Level Development Kit with Programmer	\$199

\*All prices are manufacturer's suggested resale for North America.

Microchip Technology Inc. • 2355 W. Chandler Blvd. • Chandler, AZ 85224-6199 • (480) 792-7200 • Fax (480) 792-9210

Information subject to change. The Microchip name and logo, the Microchip logo, KeELoq, MPLAB, PIC, PICmicro, PICSTART and PRO MATE are registered trademarks of Microchip Technology Inc. in the U.S.A. and other countries. FilterLab, microID, MXDEV, MXLAB, PICMASTER, SEEVAL and The Embedded Control Solutions Company are registered trademarks of Microchip Technology Inc. in the U.S.A. dsPIC, dsPICDEM.net, ECONOMONITOR, FanSense, FlexROM, fuzzyLAB, In-Circuit Serial Programming, ICSP, ICEPIC, microPort, Migratable Memory, MPASM, MPLIB, MPLINK, MPSIM, PICC, PICDEM, PICDEM.net, rPIC, Select Mode and Total Endurance are trademarks of Microchip Technology Inc. in the U.S.A. and other countries. Serialized Quick Turn Programming (SQTP) is a service mark of Microchip Technology Inc. in the U.S.A. All other trademarks mentioned herein are property of their respective companies.

© 2002 Microchip Technology Inc. All rights reserved. Printed in the U.S.A. DS30327B 9/02

