

Compact (16 mm diameter, 12 mm seated length), solar blind (spectral response: 115 to 220 nm)

The R6800U-26 is a subminiature phototube encapsulated in a TO-8 metal package. The electrode structure is designed to operate at a low voltage, allowing easy handling. Its excellent solar-blind spectral response ensures efficient UV detection without using an optical visible cut filter.

FEATURES

- Compact
- Solar Blind
- Low Voltage Operation
- Good Linearity with Respect to High Power Light

APPLICATIONS

- Laser Power Meter
 - Ar₂: 126nm
 - F₂ : 157nm
- Excimer Lamp Monitor
- UV Power Meter

GENERAL

Parameter		Description/Value	Unit
Spectral Response		115 to 220	nm
Wavelength of Maximum Response		160	nm
Photocathode	Material	Diamond (Opaque)	—
	Minimum Effective Area	φ6	mm
Window Material		MgF ₂	—

MAXIMUM RATINGS (Absolute Maximum Values)

Parameter	Value	Unit
Anode Supply Voltage	500	Vdc
Peak Cathode Current	12	μA
Average Cathode Current	4	μA
Ambient Temperature	-80 to +50	°C

CHARACTERISTICS (at +25°C)

Parameter	Value	Unit
Radiant Sensitivity (at 160 nm)	12	mA/W Typ.
Dark Current [Ⓐ]	1	pA Max.
Recommended Operating Voltage	15	Vdc

NOTE: [Ⓐ] Ebb = 15 V

METAL PACKAGE SOLAR BLIND PHOTOTUBE R6800U-26

Figure 1: Typical Spectral Response




Figure 2: Saturation Characteristics





Figure 3: Dimensional Outline (Unit: mm)



TPT A0026EA

NOTE: Don't use pins excepting ANODE and CATHODE pins.

HAMAMATSU

HAMAMATSU PHOTONICS K.K., Electron Tube Center

314-5, Shimokanzo, Toyooka-village, Iwata-gun, Shizuoka-ken, 438-0193, Japan, Telephone: (81)539/62-5248, Fax: (81)539/62-2205

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P. O. Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-2658

France: Hamamatsu Photonics France S.A.R.L.: 8, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: Lough Point, 2 Gladbeck Way, Windmill Hill, Enfield, Middlesex EN2 7JA, United Kingdom, Telephone: 44(20)8-367-3560, Fax: 44(20)8-367-6384

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171-41 SOLNA, Sweden, Telephone: (46)8-509-031-00, Fax: (46)8-509-031-01

Italy: Hamamatsu Photonics Italia: S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39)02-935 81 733, Fax: (39)02-935 81 741

TPT 1010E02
AUG. 1999 SI
Printed in Japan (500)