



RS196

Inverted Mesa Crystals Blanks

100 - 700 MHz 5.0 x 7.0mm SMD packages

XECO's RS196 Series is designed to easily fit into 5.0 x 7.0 mm package with excellent performance in terms of low spurs, frequency accuracies, and aging. The RS196 offer a smaller mesa suited for higher frequency oscillation and increased ruggedness for automatic assembly / mounting operations. XECO's proprietary process yields a mesa which is clean and free of defects, enabling high performance operation for oscillators and filters.

These devices are supplied with electrodes using XECO's proprietary process to achieve consistent C1 and C0 values as well as supplied in blank form.

Various versions to meet commercial, industrial, telecom, military temperature ranges.

Features

Stable oscillation with low spurs
4.98 mm x 2.39 mm size for 5.0 x 7.0 (7.5) mm
Electrodes in various sizes for specific frequency and C1/C0 ratios
Tune Low and Tune High options
High Q, chemically etched, free of etch channels
Mesa oriented across X-Axis

Benefits:

High volume product which fit packages and tooling
High performance operation and wide frequency of operation
Meets needs of existing designs

Applications

Crystals for precise frequency control applications in high volume packaging.
Customer applications for SONET, 10G, 1G, Storage, network communications


Operation Mode	Fundamental or Overtone
Frequency Range	100 to 700 MHz
Frequency Range 3Rd:	300 to 2.100 GHz
Frequency Tolerance	+/- 0.010 F ² (489KHz at 156.25)
Material and Q	Low Etch Channel Pure Z Quartz with a Q minimum of 1.8 Million
Surface Finish	Polished
Angle	Std AT cut 35D8' to 35D29' [EFG 3D6' t
Angle Tolerance	+/- 2' or +/- 1'
Dimensions (mm)	4.98 x 2.39 x 0.080 mm
Dimensions (inches)	0.196 x 0.094 x 0.00315"
Electrode Size	0.125mm to 1.27 mm, 5 mils to 50 mils
Electrode Style	Contacts at same end
Electrode Material	Chrome Gold or Aluminum
Electrode Freq. Tol.:	+/- 0.015 F ² (4
Contact Material:	Same as Electrode or Chrome-Gold with Aluminum
Ship Pack Method	Vacuum sealed wafflepack
Specification Note	Custom or special requirements are available

For more information, sales and technical support:



9101 W. Sahara Ave Suite 105-E10, Las Vegas, NV.
89117 Phone: 702-597-2495 Fax: 702-920-8405
Email: sales@vcamerica.com

Device Dimensions



mm		
	mm	Tolerances
X	4.978	+0.000 -0.025
Z	2.388	+0.000 -0.025
MX	1.600	+0.025 -0.025
MZ	1.600	+0.025 -0.025
ma	0.469	+0.001 -0.001
mb	0.663	+0.003 -0.003
mc	0.208	+0.001 -0.001
md	0.260	+0.001 -0.001
m:	1.079	+0.002 -0.002
tx	1.689	+0.013 -0.013
t:	0.394	+0.013 -0.013
m:	NA	NA
arcS	NA	NA

Inches		
	mils (0.001")	Tolerances
X	196.00	+0.00 -1.00
Z	94.00	+0.00 -1.00
MX	63.00	+1.00 -1.00
MZ	63.00	+1.00 -1.00
ma	18.45	+0.05 -0.05
mb	26.10	+0.10 -0.10
mc	8.20	+0.05 -0.05
md	10.25	+0.05 -0.05
m:	42.50	+0.08 -0.08
tx	66.50	+0.5 -0.5
t:	15.50	+0.5 -0.5
m:	NA	NA
arcS	NA	NA

For more information, sales and technical support: