

CMOS VOLTAGE DETECTOR

DESCRIPTION


The SCI7700Y Series/SCI7701Y Series are a series of low-power precision voltage detectors, which do not require external adjustments. The SCI7700Y Series/SCI7701Y Series have such applications as battery-life detection, power supply fault monitoring, over/under-voltage protection and battery back-up switching. The SCI7700Y Series is an open-drain Nch output type and the SCI7701Y Series is a CMOS output type. Both are available in SOT 89-3pin (plastic) packages.

FEATURES


- Many types see the next page
- Low operating supply current Typ 1.8 μ A (SCI7700YNA, V_{DD}=3.0V)
- Low range of operating voltage Typ 1.2V (SCI7700YNA)
- Temperature coefficient of detection voltage Typ (detection voltage/reference voltage) x 0.1 (mV/°C)
- Hysteresis difference Typ detection voltage x 0.05V
- Package SOT 89-3pin (plastic)

BLOCK DIAGRAM

● SCI7700Y Series




● SCI7701Y Series



November 1996

■ PIN CONFIGURATION



(Ta = 25°C)

| Type No. | Output Mode | Detection Voltage (V) | | | Operating Voltage (V) | Operating Supply Current (μA) |
|-------------|----------------|-----------------------|------|------|-----------------------|-------------------------------|
| | | Min | Typ | Max | | |
| SCI7700YVA | Open drain Nch | 0.90 | 0.95 | 1.00 | 0.8 to 5.0 | Typ 1.4 (VDD=1.5V) |
| SCI7700YAA | Open drain Nch | 1.00 | 1.05 | 1.10 | 0.9 to 5.0 | Typ 1.4 (VDD=1.5V) |
| SCI7700YAS | Open drain Nch | 1.05 | 1.10 | 1.15 | 0.8 to 10.0 | Typ 1.4 (VDD=1.5V) |
| SCI7700YBA | Open drain Nch | 1.10 | 1.15 | 1.20 | 0.9 to 5.0 | Typ 1.4 (VDD=1.5V) |
| SCI7700YNA | Open drain Nch | 1.85 | 1.90 | 1.95 | 1.2 to 10.0 | Typ 1.8 (VDD=3.0) |
| SCI7700YCA | Open drain Nch | 2.10 | 2.15 | 2.20 | 0.9 to 5.0 | Typ 1.8 (VDD=3.0V) |
| SCI7700YFA | Open drain Nch | 2.60 | 2.70 | 2.80 | 1.5 to 10.0 | Typ 1.8 (VDD=3.0V) |
| SCI7700YTA | Open drain Nch | 3.80 | 4.00 | 4.20 | 1.5 to 10.0 | Typ 2.6 (VDD=6.0V) |
| SCI7701YCA | CMOS | 2.10 | 2.15 | 2.20 | 1.5 to 10.0 | Typ 1.8 (VDD=3.0V) |
| SCI7701YCB* | | | | | | |
| SCI7701YPA | CMOS | 2.20 | 2.25 | 2.30 | 1.5 to 10.0 | Typ 1.8 (VDD=3.0V) |
| SCI7701YSA | CMOS | 2.30 | 2.35 | 2.40 | 1.5 to 10.0 | Typ 1.8 (VDD=3.0V) |
| SCI7701YEA | CMOS | 2.50 | 2.55 | 2.60 | 1.5 to 10.0 | Typ 1.8 (VDD=3.0V) |
| SCI7701YFA | CMOS | 2.60 | 2.70 | 2.80 | 1.5 to 10.0 | Typ 1.8 (VDD=3.0V) |
| SCI7701YFB* | | | | | | |
| SCI7701YRA | CMOS | 2.70 | 2.80 | 2.90 | 1.5 to 10.0 | Typ 1.8 (VDD=3.0V) |
| SCI7701YGA | CMOS | 2.90 | 3.00 | 3.10 | 1.5 to 10.0 | Typ 2.2 (VDD=4.5V) |
| SCI7701YHA | CMOS | 3.10 | 3.20 | 3.30 | 1.5 to 10.0 | Typ 2.2 (VDD=4.5V) |
| SCI7701YTA | CMOS | 3.80 | 4.00 | 4.20 | 1.5 to 10.0 | Typ 2.6 (VDD=6.0V) |
| SCI7701YMA | CMOS | 4.00 | 4.15 | 4.30 | 1.5 to 10.0 | Typ 2.6 (VDD=6.0V) |
| SCI7701YJA | CMOS | 4.30 | 4.45 | 4.60 | 1.5 to 10.0 | Typ 2.6 (VDD=6.0V) |
| SCI7701YKA | CMOS | 4.60 | 4.75 | 4.90 | 1.5 to 10.0 | Typ 2.6 (VDD=6.0V) |
| SCI7701YLA | CMOS | 4.90 | 5.10 | 5.30 | 1.5 to 10.0 | Typ 2.6 (VDD=6.0V) |

* Reverse output polarity

■ ABSOLUTE MAXIMUM RATINGS

| Parameter | Symbol | Ratings | Unit |
|--------------------------------|----------------|------------------------|------|
| Input voltage (supply voltage) | VDD (VI) – VSS | 12 | V |
| Output voltage | VO | VDD + 0.3 to VSS – 0.3 | V |
| Output current | IO | 50 | mA |
| Power dissipation (TA ≤ 25°C) | PD | 400 | mW |
| Operating temperature | Topr | –30 to 85 | °C |
| Storage temperature | Tstg | –65 to 150 | °C |
| Soldering temperature and time | Tsol | 260°C, 10s (at lead) | — |

Note: Although this IC has electrostatic protection circuit, damage may still occur if very high electrostatic potentials are applied.

Note: When this IC is soldered in the solder-reflow process, be sure to maintain the reflow furnace at the curve shown in “Fig. 3–5 Reflow Furnace Temperature Curve” of DATA BOOK. This IC cannot be exposed to the high temperature of the the solder dipping.

November 1996

■ ELECTRICAL CHARACTERISTICS

● SCI7700YSeries/SCI7701YSeries

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|---|--|---|--|-------------------------|-----|-------|
| Detection voltage | V _{DET} | T _a =25°C | See page 2 | | | V |
| Operating supply current | I _{DDO} | V _{DD} =1.5V, T _a =25°C | — | 1.4 | 3.0 | μA |
| | | V _{DD} =3.0V, T _a =25°C | — | 1.8 | 4.0 | |
| | | V _{DD} =4.5V, T _a =25°C | — | 2.2 | 5.0 | |
| | | V _{DD} =6.0V, T _a =25°C | — | 2.6 | 6.0 | |
| Supply (Operating) voltage | V _{DD} (V _I) | T _a =-30 to 85°C | See page 2 | | | V |
| Hysteresis difference | ΔV _{DET} | T _a =-30 to 85°C | — | V _{DET} x0.05* | — | V |
| Temperature coefficient of V _{DET} | $\frac{V_{DET}(T_a=70^\circ C)-V_{DET}(T_a=20^\circ C)}{90}$ | T _a =-30 to 85°C | Typ(V _{DET} /V _R)x0.1 | | | mV/°C |
| | 90 | | | | | |

* V_{DET} x 0.04 (Typ) about SCI7700Y_{TA}/SCI7701Y_{TA}/SCI7701Y_{MA}/SCI7701Y_{JA}/SCI7701Y_{KA}/SCI7701Y_{LA}

● SCI7700Y_{VA}/SCI7700Y_{AA}/SCI7700Y_{BA}

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|--------------------------|----------------------|--|------|------|------|------|
| Output current | | V _{DD} = 0.85V, V _{DS} = 0.5V, T _a = 25°C | 0.05 | 0.40 | 1.00 | mA |
| | I _O (Nch) | V _{DD} = 0.95V, V _{DS} = 0.5V, T _a = 25°C | 0.15 | 0.70 | 1.50 | |
| | | V _{DD} = 1.05V, V _{DS} = 0.5V, T _a = 25°C | 0.30 | 1.00 | 2.00 | |
| Reference voltage supply | V _R | T _a = 25°C | 0.70 | 0.80 | 0.90 | V |

V_{DS}: Voltage between drain and source

■ ELECTRICAL CHARACTERISTICS (Cont.)

- SCI7700YNA/SCI7700YTA/SCI7701YCA/SCI7701YPA/SCI7701YSA/SCI7701YEA/SCI7701YFA/
SCI7701YRA/SCI7701YGA/SCI7701YHA/SCI7701YTA/SCI7701YMA/SCI7701YJA/SCI7701YKA/
SCI7701YLA

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|--------------------------|----------|------------------------------|------|------|--------|------|
| Output current | Io (Nch) | VDD=0.95V, VDS=0.5V, Ta=25°C | 0.03 | 0.15 | 0.50 | mA |
| | | VDD=1.00V, VDS=0.5V, Ta=25°C | 0.05 | 0.22 | 0.60 | |
| | | VDD=1.20V, VDS=0.5V, Ta=25°C | 0.30 | 0.70 | 1.50 | |
| | | VDD=2.40V, VDS=0.5V, Ta=25°C | 1.40 | 2.00 | 2.30*1 | |
| | | VDD=3.60V, VDS=0.5V, Ta=25°C | 1.50 | 2.30 | 2.60*2 | |
| | Io (Pch) | VDD=4.50V, VDS=2.1V, Ta=25°C | 1.7 | 2.0 | 2.3 | |
| | | VDD=8.00V, VDS=2.1V, Ta=25°C | 2.8 | 3.1 | 3.8 | |
| Reference voltage supply | VR | Ta=25°C | 0.90 | 1.00 | 1.10 | V |

- * 1: 3.30 mA about SCI7700YTA, * 2: 4.00 mA about SCI7700TA VDS: Voltage between drain and source
- * Please inquire IC sales department about SCI7700YCA.



- SCI7700YAS/SCI7700YFA/SCI7701YCB/SCI7700YFB

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|--------------------------|----------|--------------------------------|------|-----|-----|------|
| Output current | Io (Nch) | VDD=0.8V, VOUT=0.1V, Ta=25°C*1 | 0.01 | — | — | mA |
| | | VDD=2.4V, VOUT=0.5V, Ta=25°C*2 | 1.7 | 2.5 | 3.3 | |
| | | VDD=2.4V, VOUT=0.5V, Ta=25°C*3 | 1.4 | 1.8 | 2.3 | |
| | | VDD=3.0V, VOUT=0.5V, Ta=25°C*4 | 1.5 | 2.0 | 2.5 | |
| | Io (Pch) | VDD=2.0V, VOUT=1.5V, Ta=25°C*3 | 0.1 | 0.3 | 0.9 | |
| | | VDD=2.0V, VOUT=1.5V, Ta=25°C*4 | 0.1 | 2.0 | 2.5 | |
| Reference voltage supply | VR | Ta=25°C*1 | 0.7 | 0.8 | 0.9 | V |
| | | Ta=25°C*2,*3,*4 | 0.9 | 1.0 | 1.1 | |

- * 1: Applicable to SCI7700YAS
- * 2: Applicable to SCI7700YFA
- * 3: Applicable to SCI7701YCB
- * 4: Applicable to SCI7701YFB


November 1996

■ PERFORMANCE CURVES




MARKING

An abbreviation is printed on SCI7700Yseries/SCI7701Yseries below, because its package size is very small.



PACKAGE DIMENSIONS



November 1996

| | | | |
|---|--|--|---|
| West Coast S-MOS Systems, Inc. 150 River Oaks Parkway San Jose, CA 95134 Tel. (408) 922-0200 Fax (408) 922-0238 | North East and North Central S-MOS Systems, Inc. 301 Edgewater Place, Suite 120 Wakefield, MA 01880 Tel. (617) 246-3600 Fax (617) 246-5443 | South East and South Central S-MOS Systems, Inc. 4300 Six Forks Road, Suite 430 Raleigh, NC 27609 Tel. (919) 781-7667 Fax (919) 781-6778 | More info... World Wide Web: http://www.smos.com |
|---|--|--|---|

S-MOS assumes no responsibility or liability for (1) any errors or inaccuracies contained in the information herein and (2) the use of the information or a portion thereof in any application, including any claim for (a) copyright or patent infringement or (b) direct, indirect, special or consequential damages. There are no warranties extended or granted by this document. The information herein is subject to change without notice from S-MOS.