


# SBD Type : TCH10A15-11A

OUTLINE DRAWING

## FEATURES

- \*Tabless TO-220
- Packaged in 24mm Tape and Reel
- \*Dual Diodes – Cathode Common
- \*Low Forward Voltage Drop
- \*High Surge Capability
- \*T<sub>j</sub>=150 °C operation



## Maximum Ratings


Approx Net Weight: 1.45g

Rating	Symbol	TCH10A15-11A		Unit
Repetitive Peak Reverse Voltage	V <sub>RRM</sub>	150		V
Average Rectified Output Current	I <sub>O</sub>	10	T <sub>c</sub> =121°C 50 Hz Full Sine Wave Resistive Load	A
RMS Forward Current	I <sub>F(RMS)</sub>	11.1		A
Surge Forward Current	I <sub>FSM</sub>	130	50Hz Full Sine Wave ,1cycle Non-repetitive	A
Operating JunctionTemperature Range	T <sub>jw</sub>	-40 to +150		°C
Storage Temperature Range	T <sub>stg</sub>	-40 to +150		°C


## Electrical • Thermal Characteristics

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Unit
Peak Reverse Current	I <sub>RM</sub>	T <sub>j</sub> = 25°C, V <sub>RM</sub> = V <sub>RRM</sub> per arm	-	-	1	mA
Peak Forward Voltage	V <sub>FM</sub>	T <sub>j</sub> = 25°C, I <sub>FM</sub> = 5 A per arm	-	-	0.88	V
Thermal Resistance (Junction to Case)	R <sub>th(j-c)</sub>	Junction to Case	-	-	3	°C /W


C\_T\_ 11A OUTLINE DRAWING (Dimensions in mm)



FORWARD CURRENT VS. VOLTAGE




AVERAGE FORWARD POWER DISSIPATION



PEAK REVERSE CURRENT VS. PEAK REVERSE VOLTAGE


T<sub>j</sub> = 150 °C

TCH10A15/TCH10A15-11A (per Arm)



AVERAGE REVERSE POWER DISSIPATION

TCH10A15/TCH10A15-11A (Total)






### AVERAGE FORWARD CURRENT VS. CASE TEMPERATURE

$V_{RM} = 150V$


TCH10A15/TCH10A15-11A (Total)



### SURGE CURRENT RATINGS

f=50Hz, Sine Wave, Non-Repetitive, No Load

TCH10A15/TCH10A15-11A



JUNCTION CAPACITANCE VS. REVERSE VOLTAGE

$T_j=25^\circ\text{C}$ ,  $V_m=20\text{mV}_{\text{RMS}}$ ,  $f=100\text{kHz}$ , Typical Value

TCH10A15/TCH10A15-11A (per Arm)

