

**VI TELEFILTER****Filter specification****TFS 285****1/5****Measurement condition**

Ambient temperature:	23 °C
Input power level:	0 dBm
Terminating impedance	
Input	30 Ω    -21.2 pF
Output	35 Ω    -21.6 pF

**Characteristics**

## Remark:

Reference level for the relative attenuation  $a_{rel}$  of the TFS 285 is the minimum of the pass band attenuation  $a_{min}$ . The minimum of the pass band attenuation  $a_{min}$  is defined as the insertion loss  $a_e$ . The centre frequency  $f_o$  is the arithmetic mean value of the upper and lower frequencies at the 30 dB filter attenuation level relative to the insertion loss  $a_e$ . The nominal frequency  $f_N$  is fixed on 285 MHz without tolerance. The given values for the relative attenuation  $a_{rel}$  and for the group delay ripple have to be reached at the frequencies given below also if the centre frequency  $f_o$  is shifted due to the temperature coefficient of frequency  $TC_f$  in the operating temperature range and due to a production tolerance for the centre frequency  $f_o$

D a t a		typ. value		tolerance / limit	
<b>Insertion loss</b> (Reference level)	$a_e = a_{min}$	9,5	dB	max. 12	dB
<b>Nominal frequency</b>	$f_N$	-		285	MHz
<b>Pass band</b>					
Pass band ripple	$f_N \pm 7,5$ MHz	0,8	dB	max. 1,2	dB
Passband width	3 dB			min. 20	MHz
<b>Group delay</b> GD					
Group delay ripple	$f_N \pm 7,5$ MHz	90	ns	max. 150	ns
<b>Relative attenuation</b>	$a_{rel}$				
$f_N - 75$ MHz ...	$f_N - 20$ MHz	38	dB	min. 30	dB
$f_N + 20$ MHz ...	$f_N + 75$ MHz	38	dB	min. 30	dB
<b>VSWR ratio</b>					
at $f_N - 7,5$ MHz ...	$f_N + 7,5$ MHz	-		max. 2 : 1	
<b>Operating temperature range</b>				- 5 °C ... + 85 °C	
<b>Temperature coefficient of frequency</b>	$TC_f$	- 72	ppm/K		
<b>Input power level</b>				max. + 10	dBm

Generated: \_\_\_\_\_


Checked / approved: \_\_\_\_\_

VI TELEFILTER  
 Potsdamer Straße 18  
 D 14 513 TELTOW / Germany  
 Tel: (+49) 3328 4784-52 / Fax: (+49) 3328 4784-30  
 E-Mail: tft@telefilter.com

Vectron International, Inc.  
 267 Lowell Road  
 Hudson, NH 03051 / USA  
 Tel: (603) 598-0070 Fax: (603) 598-0075  
 E-Mail: vti@vtinh.com


VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

## Construction and pin connection



1	Ground
2	Ground
3	Output RF Return
4	Output
5	Package Ground
6	Ground
7	Ground
8	Ground
9	Input RF Return
10	Input
11	Package Ground
12	Ground

Datecode:	Year+week
K	1998
L	1999
M	2000
...	

50  $\Omega$  test circuit

VI TELEFILTER  
 Potsdamer Straße 18  
 D 14 513 TELTOW / Germany  
 Tel: (+49) 3328 4784-52 / Fax: (+49) 3328 4784-30  
 E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)

Vectron International, Inc.  
 267 Lowell Road  
 Hudson, NH 03051 / USA  
 Tel: (603) 598-0070 Fax: (603) 598-0075  
 E-Mail: [vti@vtinh.com](mailto:vti@vtinh.com)

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

**VI TELEFILTER****Filter specification****TFS 285****3/5****Stability Characteristics:**

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 18 ms, half sine wave, 3 shocks each plane;  
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5g respectively, 1 octave per min, 10 cycles per plan, 3 plans;  
DIN IEC 68 T2 - 6
3. Damp heat: 25 °C to 55°C / 95% r.H. / 10 cycles  
(cycle) DIN IEC 68 - 2 – 30 Db
4. Resistance to solder heat (reflow): max. 2 times reflow process;  
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;


**Packing:**

Tape & Reel: IEC 286 - 3, with exception of value for N and minimum bending radius;  
tape type II, embossed carrier tape with top cover tape on the upper side;


max. pieces of filters per reel: 3000  
Reel of empty components at start: min 300 mm  
Reel of empty components at start including leader: min 500 mm  
Trailer min 300 mm

**Tape (all dimensions in mm)**

W	: 16 ±0,3
Po	: 4 ±0,1
Do	: 1,5 +0,5
E	: 1,75 ±0,1
F	: 7,5 ±0,1
G (min)	: 0,6
P2	: 2 ±0,1
P1	: 8 ±0,1
D1(min)	: 1,5
Ao	: 5,5 ±0,1
Bo	: 7,5 ±0,1
Ct	: 13,5+/-0,1

**Reel (all dimensions in mm):**

A	:	330
W1	:	16,4 +2
W2 (max)	:	22,4
N (min)	:	50
C	:	13 + 0,5
		- 0,2



The minimum bending radius is 45 mm. The mounting surface of the filters faces the bottom side of the embossed carrier tape. The marking of the filters is readable if the sprocket holes are on the left side of the tape, i.e. pin 1 identifier is close to the sprocket holes.

**VI TELEFILTER**  
**Potsdamer Straße 18**  
**D 14 513 TELTOW / Germany**  
**Tel: (+49) 3328 4784-52 / Fax: (+49) 3328 4784-30**  
**E-Mail: tft@telefilter.com**

**Vectron International, Inc.**  
**267 Lowell Road**  
**Hudson, NH 03051 / USA**  
**Tel: (603) 598-0070 Fax: (603) 598-0075**  
**E-Mail: vti@vtinh.com**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

## Air reflow temperature conditions

## 1st and 2nd air reflow profile

Name:	pre-heating periods	main-heating periods	peak temperature
Temperature:	150 °C - 170 °C	over 200 °C	255 °C ± 5 °C
Time:	60 sec. - 90 sec.	20 sec. - 25 sec.	

## Air reflow profile




Table for temperature vs. time during the air reflow process

Tolerance of temperatures: ± 5 °C

time / sec.	temperature / °C	time / sec.	temperature / °C
0	23	140	160
10	34	150	161
20	46	160	164
30	60	170	170
40	80	180	180
50	103	190	205
60	121	195	230
70	134	200	255
80	143	205	230
90	150	210	205
100	154	215	180
110	156	220	165
120	158	230	140
130	159	240	120

**VI TELEFILTER****Filter specification****TFS 285****5/5****History**

<b>Version</b>	<b>Reason of Changes</b>	<b>Name</b>	<b>Date</b>
1.0	- development specification	Steiner	03.03.2000
2.0	- complete specification (tape&reel,terminating impedances matching, soldering profile, new date code added)	Steiner	07.07.2000
	- loss corrected from 10,5 dB to 12 dB according to Nortel Specification	Steiner	07.07.2000

**VI TELEFILTER**  
**Potsdamer Straße 18**  
**D 14 513 TELTOW / Germany**  
**Tel: (+49) 3328 4784-52 / Fax: (+49) 3328 4784-30**  
**E-Mail: tft@telefilter.com**

**Vectron International, Inc.**  
**267 Lowell Road**  
**Hudson, NH 03051 / USA**  
**Tel: (603) 598-0070 Fax: (603) 598-0075**  
**E-Mail: vti@vtinh.com**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.