

(TLP3061)

- OFFICE MACHINE
- HOUSEHOLD USE EQUIPMENT
- TRIAC DRIVER
- SOLID STATE RELAY

The TOSHIBA TLP3061, TLP3062 and TLP3063 consist of a zero voltage crossing turn-on photo-triac optically coupled to a gallium arsenide infrared emitting diode in a six lead plastic DIP package.

- Peak Off-State Voltage : 600V (Min.)
- Trigger LED Current : 15mA (Max.) (TLP3061)
10mA (Max.) (TLP3062)
5mA (Max.) (TLP3063)
- On-State Current : 100mA (Max.)
- UL Recognized : UL1577, File No. E67349
Isolation Voltage : 5000Vrms (Min.)
- Option (D4) type VDE Approved : DIN VDE0884/08.87,
Certificate No. 68329


Maximum Operating Insulation Voltage : 630V_{PK}
 Highest Permissible Over Voltage : 6000V_{PK}

(Note) When a VDE0884 approved type is needed, please designate the "Option (D4)"


	7.62mm pich standard type	10.16mm pich (LF2) type
Creepage Distance	7.0mm (Min.)	8.0mm (Min.)
Clearance	7.0mm (Min.)	8.0mm (Min.)
Insulation Thickness	0.5mm (Min.)	0.5mm (Min.)

- Creepage Distance : 7.0mm (Min.) 8.0mm (Min.)
- Clearance : 7.0mm (Min.) 8.0mm (Min.)
- Insulation Thickness : 0.5mm (Min.) 0.5mm (Min.)

Unit in mm



PIN CONFIGURATION (TOP VIEW)



- 1 : ANODE
- 2 : CATHODE
- 3 : N.C.
- 4 : TERMINAL 1
- 6 : TERMINAL 2

© The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
 © These TOSHIBA products are intended for use in general commercial applications (office equipment, communication equipment, measuring equipment, domestic appliances, etc.), please make sure that you consult with us before you use these TOSHIBA products in equipment which requires extraordinarily high quality and/or reliability, and in equipment which may involve life threatening or critical application, including but not limited to such uses as atomic energy control, airplane or spaceship instrumentation, traffic signals, medical instrumentation, combustion control, all types of safety devices, etc. TOSHIBA cannot accept and hereby disclaims liability for any damage which may occur in case the TOSHIBA products are used in such equipment or applications without prior consultation with TOSHIBA.

(TLP3061)

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT	
LED	Forward Current	I _F	50	mA	
	Forward Current Derating (Ta ≥ 53°C)	ΔI _F /°C	-0.7	mA/°C	
	Peak Forward Current (100μs pulse, 100pps)	I _{FP}	1	A	
	Power Dissipation	P _D	100	mW	
	Power Dissipation Derating (Ta ≥ 25°C)	ΔP _D /°C	-1.0	mW/°C	
	Reverse Voltage	V _R	5	V	
	Junction Temperature	T _j	125	°C	
DETECTOR	Off-State Output Terminal Voltage	V _{DRM}	600	V	
	On-State RMS Current	Ta = 25°C	I _T (RMS)	100	mA
		Ta = 70°C		50	
	On-State Current Derating (Ta ≥ 25°C)	ΔI _T /°C	-1.1	mA/°C	
	Peak On-State Current (100μs pulse, 120pps)	I _{TP}	2	A	
	Peak Nonrepetitive Surge Current (P _w = 10ms, DC = 10%)	I _{TSM}	1.2	A	
	Power Dissipation	P _D	300	mW	
	Power Dissipation Derating (Ta ≥ 25°C)	ΔP _D /°C	-4.0	mW/°C	
	Junction Temperature	T _j	115	°C	
	Storage Temperature Range	T _{stg}	-55~150	°C	
	Operating Temperature Range	T _{opr}	-40~100	°C	
	Lead Soldering Temperature (10s)	T _{sol}	260	°C	
Total Package Power Dissipation	P _T	330	mW		
Total Package Power Dissipation Derating (Ta = 25°C)	ΔP _T /°C	-4.4	mW/°C		
Isolation Voltage (AC, 1min., R.H. ≤ 60%)	(Note 1) BV _S	5000	V _{rms}		

Note 1 : Device considered a two terminal device : Pins 1, 2 and 3 shorted together and pins 4 and 6 shorted together.

TLP3061 - 2
1996 - 4 - 8
TOSHIBA CORPORATION

(TLP3061)

INDIVIDUAL ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
LED	Forward Voltage	V_F	$I_F = 10\text{mA}$	1.0	1.15	1.3	V
	Reverse Current	I_R	$V_R = 5\text{V}$	—	—	10	μA
	Capacitance	C_T	$V = 0, f = 1\text{MHz}$	—	10	—	pF
DETECTOR	Peak Off-State Current	I_{DRM}	$V_{DRM} = 600\text{V}$	—	10	1000	nA
	Peak On-State Voltage	V_{TM}	$I_{TM} = 100\text{mA}$	—	1.7	3.0	V
	Holding Current	I_H	—	—	0.6	—	mA
	Critical Rate of Rise of Off-State Voltage	dv/dt	$V_{in} = 240\text{Vrms}, T_a = 85^\circ\text{C}$ (Fig.1)	200	500	—	$\text{V}/\mu\text{s}$
	Critical Rate of Rise of Commutating Voltage	$dv/dt(c)$	$V_{in} = 60\text{Vrms}, I_T = 15\text{mA}$ (Fig.1)	—	0.2	—	$\text{V}/\mu\text{s}$

COUPLED ELECTRICAL CHARACTERISTICS (Ta = 25°C)


CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Trigger LED Current	TLP3061	I_{FT}	$V_T = 6\text{V}$	—	—	15	mA
	TLP3062			—	5	10	
	TLP3063			—	—	5	
Inhibit Voltage	V_{IH}	$I_F = \text{Rated } I_{FT}$	—	—	50	V	
Leakage in Inhibited State	I_{IH}	$I_F = \text{Rated } I_{FT}$ $V_T = \text{Rated } V_{DRM}$	—	100	300	μA	
Capacitance Input to Output	C_S	$V_S = 0, f = 1\text{MHz}$	—	0.8	—	pF	
Isolation Resistance	R_S	$V_S = 500\text{V (R.H. } \leq 60\%)$	5×10^{10}	10^{14}	—	Ω	
Isolation Voltage	BV_S	AC, 1 minute	5000	—	—	Vrms	
		AC, 1 second, in oil	—	10000	—		
		DC, 1 minute, in oil	—	10000	—	V _{dc}	

RECOMMENDED OPERATING CONDITIONS







CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage	V_{AC}	—	—	240	Vac
Forward Current	I_F^*	15	20	25	mA
Peak On-State Current	I_{TP}	—	—	1	A
Operating Temperature	T_{opr}	-25	—	85	°C

* In the case of TLP3062

Fig. 1 dv/dt TEST CIRCUIT



(TLP3061)



(TLP3061)

