



LOW PROFILE Transformer for printed circuit mounting.

- Five sizes: 2, 6, 12, 24 and 48 VA ratings.
- Split bobbins for increased dielectric strength and low capacitive coupling.
- 115/230 volts, 47/63 Hz primary windings.
- CSA listed (LR 47366) and U.L. recognized (E100878).



MECHANICAL



Dimensions, Inches

Size	A	B	C	D	E	S
4701	1.56	1.88	0.65	0.375	1.60	0.028 X 0.041
4702	1.56	1.88	0.85	0.375	1.60	0.028 X 0.041
4703	2.00	2.50	1.07	0.50	2.00	0.028 X 0.041
4704	2.25	2.87	1.25	0.60	1.90	0.040 X 0.040
4705	2.50	3.12	1.38	0.60	2.18	0.040 X 0.040

ELECTRICAL SPECIFICATION

Part No.	VA	Parallel		Series	
		Volts	Amps	Volts	Amps
4701-05	2	5	0.50	10	0.25
4701-06	2	6.3	0.40	12.6	0.20
TLP4701-08	2	8	0.30	16	0.15
4701-10	2	10	0.25	20	0.13
4701-12	2	12	0.20	24	0.10
4701-15	2	15	0.17	30	0.09
4701-17	2	17	0.15	34	0.08
4701-28	2	28	0.09	56	0.05
4702-05	6	5	1.20	10	0.60
4702-06	6	6.3	0.90	12.6	0.45
4702-08	6	8	0.70	16	0.35
4702-10	6	10	0.60	20	0.30
4702-12	6	12	0.50	24	0.25
4702-15	6	15	0.40	30	0.20
4702-17	6	17	0.34	34	0.17
4702-28	6	28	0.20	56	0.10
4703-05	12	5	2.40	10	1.20
4703-06	12	6.3	1.80	12.6	0.90
4703-08	12	8	1.40	16	0.70
4703-10	12	10	1.20	20	0.60
4703-12	12	12	1.00	24	0.50
4703-15	12	15	0.80	30	0.40
4703-17	12	17	0.68	34	0.34
4703-28	12	28	0.40	56	0.20

Part No.	VA	Parallel		Series	
		Volts	Amps	Volts	Amps
4704-05	24	5	4.80	10	2.40
4704-06	24	6.3	3.80	12.6	1.90
4704-08	24	8	3.00	16	1.50
4704-10	24	10	2.40	20	1.20
4704-12	24	12	2.00	24	1.00
4704-15	24	15	1.60	30	0.80
4704-17	24	17	1.40	34	0.70
4704-28	24	28	0.85	56	0.43
4705-05	48	5	9.60	10	4.80
4705-06	48	6.3	7.60	12.6	3.80
4705-08	48	8	6.00	16	3.00
4705-10	48	10	4.80	20	2.40
4705-12	48	12	4.00	24	2.00
4705-15	48	15	3.20	30	1.60
4705-17	48	17	2.80	34	1.40
4705-28	48	28	1.70	56	0.83