



- NOTES:
1. DISPLAY TYPE: 600
  2. VIEWING DIRECTION: TRANSMISSIVE/NEGATIVE
  3. POLARIZER MODE: 1/240 DUTY
  4. DRIVE METHOD: 1/15 BIAS
  5. VEE: 21.6V
  6. VDD: 5.0V
  7. OPERATING TEMP: -25°C~+55°C
  8. STORAGE TEMP: -35°C~+65°C
  9. DRIVER: LH156GF4
  10. BACKLIGHT: CFL(LAC/780V(TYP.), SNAK(TYP)) WHITE
  11. BEZEL IS STAINLESS STEEL
  12. ALL UNMARKED TOLERANCES: ±0.3mm

DETAIL A:



COLOR FILTER



BLACK MASK

CON 1		CON 2	
PIN	SYMBOL	PIN	SYMBOL
1	N	1	VFL1
2	YD	2	NC
3	LP	3	VFL2
4	XCK		
5	DISPDT		
6	VDD		
7	VSS		
8	VEE		
9	D7		
10	D6		
11	D5		
12	D4		
13	D3		
14	D2		
15	D1		
16	D0		



**TIAN-MA MICROELECTRONICS CO.**

2E/F, HANGOU Building, Shennan Road, Central, Shenzhen, China

DRAWN BY:	BY:	TITLE: TM320240AKGV/T3	SCALE:	1:1
CHECKED BY:	BY:	DWG NO: G-1	UNIT:	mm
APPROVED BY:	BY:	DWG NAME: TM320240AKGV/T3	SHEET NO:	1 OF 1
CONFIRMED BY:	BY:			