

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The ASI VHB25-28F is Designed for

FEATURES:

-
-
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	4.0 A
V_{CB0}	65 V
V_{EBO}	4.0 V
V_{CEO}	35 V
P_{DISS}	40 W @ T _C = 25 °C
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +150 °C
θ_{JC}	4.4 °C/W

PACKAGE STYLE .380 4L FLG

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.220 / 5.59	.230 / 5.84
B	.785 / 19.94	
C	.720 / 18.29	.730 / 18.54
D	.970 / 24.64	.980 / 24.89
E		.385 / 9.78
F	.004 / 0.10	.006 / 0.15
G	.085 / 2.16	.105 / 2.67
H	.160 / 4.06	.180 / 4.57
I		.280 / 7.11
J	.240 / 6.10	.255 / 6.48

ORDER CODE: ASI10724

CHARACTERISTICS T_C = 25 °C

SYMBOL	TEST CONDITIONS			MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CEO}	I _C = 200 mA			35			V
BV_{CES}	I _C = 200 mA			65			V
BV_{EBO}	I _E = 10 mA			4.0			V
I_{CB0}	V _E = 30 V					2.0	mA
h_{FE}	V _{CE} = 5.0 V	I _C = 200 mA		5.0		---	---
C_{ob}	V _{CB} = 28 V	f = 1.0 MHz				50	pF
f_T	V _{CE} = 10 V	I _C = 200 mA	f = 100 MHz	250			MHz
P_G η_C	V _{CC} = 28 V	P _{OUT} = 25 W	f = 175 MHz	8.5	60		dB %