

XO3070 Series

1x1 inch, 5.0 Volt, TTL/HCMOS/Sinewave, TCXO


- All output types
- Low power, high stability

Model	Frequency (MHz)	Temperature Range (°C)	Temperature Stability	Aging First Year	Output	Supply Voltage
XO3070	20	-30 to +90	±1.0 ppm	±1.0 ppm	HCMOS	5 V ±0.25 V
XO3071	20	-30 to +90	±1.0 ppm	±1.0 ppm	Sinewave	5 V ±0.25 V
Options	10 to 100	See Table		Frequency Dependent	Sine, TTL, ACMOS	5 V to 15 V

Additional Specifications	
Aging over ten years	±3.0 ppm max
Current	
Sine	As low as 2 mA
HCMOS	12 mA
Frequency Adjust	Internal *(XO3070)
Method	External 0 to 5 V or potentiometer **(XO3071)
Range	10 Years
Output	
Level	HCMOS
Load	2 Gates
Sine Wave Option	
Level	0 to +3 dBm (50 Ω)
Load	1 k Ω//10pF
Environmental	
Vibration	10 g pk, 10-2000 Hz
Shock	50 g 11 mS 1/2 Sine
Phase Noise @ 20 MHz	
10 Hz	-85 dBc/Hz
100 kHz	-120 dBc/Hz
1 kHz	-140 dBc/Hz
10 kHz	-150 dBc/Hz

Optional Temperature Range (°C)	±1	±0.75	±0.50	±0.25
+15 to +30	✓	✓	✓	✓
0 to +50	✓	✓	✓	✓
0 to +70	✓	✓	✓	✓
-20 to +70	✓	✓	✓	✓
-40 to +75	✓	✓	✓	✓
-55 to +85	✓	✓	✓	✓


This TCXO can be produced to these specifications, with extended temperature range and tighter stability being cost drivers.



Dimensions are in inches (mm)

Pin connections
1. CASE GROUND & SUPPLY RETURN
2. RF OUTPUT
3. SUPPLY (+)
4. CASE GROUND OR FREQ. ADJUST

Pin numbers shown for ref. only.
Numbers are not marked on unit.



* Internal Adjust
** External Adjust

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.